

DATA SHEET

PD-C 360/24 Slave

Order description

PD-C 360/24 Slave white

Item number

EP10055386

GTIN

4015120055386



Product description

- "Slave" presence detector for extending the field of detection of a "master" presence detector with 360° field of detection for ceiling mounting
- range of up to 24 m in diameter as a cost efficient system upgrade with up to 10 additional extensions
- Ideal for use in areas with ceilings of up to 10 m, such as sports halls, warehouses etc.
- Connection of the "Slave" detector to many presence detectors of the PD-C series possible



Technical data

GENERAL	
Conformity	CE, RoHS, SundaHus, WEEE
Warranty	5 years
ATTACHMENT	
Installation type	Recessed mounting
Installation position	Ceiling
Installation dimension	Installation depth: 24 mm, Ø 60 mm
HOUSING	
Dimensions	Height/Depth 70 mm, Ø 108 mm
Weight	129 g
Material	UV-stabilised polycarbonate
Protection type	recessed-mounted IP20, IP20/IP54 with surface-mounted box (order separately), IP20 as recessed ceiling-mounted version (order installation set separately)
Permissible ambient temperature	-25 °C...+50 °C
Relative humidity	5 - 93 %, non-condensing
Colour	white, similar to RAL 9010
Connection	2,5 mm² / 1,5 mm²
ELECTRICAL VERSION	
Protection class	II
Nominal voltage	230 V / 50 Hz
Power consumption	0,3 W

SENSORS	
Detection angle	360°
Detection range diagonally	Ø 24 m
Detection range head-on	Ø 11 m
Detection range presence	Ø 8 m
Field of detection	up to 453 m²
Recommended installation height	3 m
Max. mounting height	10 m
Light measurement	none
Push button input HVAC	false
Slave input	yes
Fully automatic	No
Semi-automatic	No
constant lighting control	false
Switching delay from "dark to light" [s]	300 s
Switching delay from "light to dark" [s]	30 s
CONTROL	
Channel 1	Presence
Interface	Not relevant
Contact	Bus system
Switch-off delay time	Not relevant
Master/slave function	true
constant lighting control	false
Presence simulation	false
Manual override	No

PD-C 360/24 Slave

Order description	Item number	GTIN
PD-C 360/24 Slave white	EP10055386	4015120055386

Scale drawing	Field of detections
	 Operating area approx. Ø 8 m Head-on to detector approx. Ø 11 m Passage area / diagonally to detector approx. Ø 24 m