

## PD-C 360/8 mini Slave

### Order description

PD-C360/8 mini slave

### Item number

EP10426063

### GTIN

4015120426063



### Product description

- "Slave" presence detector for extending the field of detection of a "master" presence detector with 360° field of detection for ceiling mounting
- Range of up to 8 m in diameter as a cost efficient system upgrade with up to 10 additional extensions
- "Slave" detector can be connected to the following models:
  - PD-C360i/8 mini / PD-C360i/8 mini-3m / PD-C360i/8 mini DIM
  - PD-C360i/12 mini / PD-C360i/12 mini DIM

### Technical data

GENERAL	
Conformity	CE, RoHS, WEEE
Warranty	5 years
ATTACHMENT	
Installation type	Recessed mounting
Installation position	Ceiling
Installation dimension	Installation depth: 45 mm, Ø 25 mm
HOUSING	
Dimensions	Height/Depth 60 mm, Ø 33 mm
Weight	83 g
Material	UV-stabilised PE, UV-stabilised polycarbonate
Protection type	IP55
Permissible ambient temperature	-25 °C...+50 °C
Relative humidity	5 - 93 %, non-condensing
Colour	Opal matt
Connection	1.5 mm <sup>2</sup>
ELECTRICAL VERSION	
Protection class	II
Nominal voltage	230 V / 50 Hz
Supply line	60 cm, 3 x 1.00 mm <sup>2</sup>
Power consumption	0,2 W


SENSORS	
Detection angle	360°
Detection range diagonally	Ø 8 m
Detection range head-on	Ø 5 m
Detection range presence	Ø 3 m
Field of detection	up to 50 m <sup>2</sup>
Recommended installation height	3 m
Max. mounting height	5 m
Light measurement	none
Push button input HVAC	false
Slave input	yes
Fully automatic	No
Semi-automatic	No
constant lighting control	false
Switching delay from "dark to light" [s]	0 s
Switching delay from "light to dark" [s]	30 s
CONTROL	
Channel 1	Presence
Interface	Not relevant
Contact	Bus system
Switch-off delay time	Not relevant
Master/slave function	false
constant lighting control	false
Manual override	No

# DATA SHEET


## PD-C 360/8 mini Slave

Order description	Item number	GTIN
PD-C360/8 mini slave	EP10426063	4015120426063

### Scale drawing



### Field of detections



- Operating area approx.  $\varnothing$  3 m
- Head-on to detector approx.  $\varnothing$  5 m
- Passage area / diagonally to detector approx.  $\varnothing$  8 m