DATA SHEET



PD-FLAT 360i/8 ROUND WHITE DALI SET

Order description GTIN Item number

4015120428708 PD-FLAT-S 360i/8 RW DALI EP10428708





















Product description

- DALI design presence detector with excellent detection capabilities, at least 8 m in diameter
- Low profile design with plastic design covers: round, white variably interchangeable (alternatively: square, glass, black)
- Set: DALI bus power supply 200 mA included in delivery

Technical data

| GENERAL | |
|---------------------------------|------------------------------------|
| Conformity | CE, RoHS, WEEE |
| Warranty | 5 years |
| ATTACHMENT | |
| Installation type | Recessed mounting |
| Installation position | Ceiling |
| Installation dimension | Installation depth: 24 mm, Ø 60 mm |
| HOUSING | |
| Dimensions | Height/Depth 30 mm, Ø 94 mm |
| Weight | 80 g |
| Material | UV-stabilised polycarbonate |
| Protection type | IP20 |
| Permissible ambient temperature | 0 °C+50 °C |
| Relative humidity | 5 - 93 %, non-condensing |
| Colour | white, similar to RAL 9010 |
| Connection | 2,5 mm² / 1,5 mm² |
| ELECTRICAL VERSION | |
| Protection class | III |
| Nominal voltage | 230 V / 50 - 60 Hz |
| Power consumption | 0,3 W |
| Power consumption | 12 mA |
| SENSORS | |
| Detection angle | 360° |
| Detection range diagonally | Ø 8 m |

| Detection range head-on | Ø 6 m |
|--|---------------|
| Detection range presence | Ø 4 m |
| Field of detection | up to 50 m² |
| Recommended installation height | 2,5 m |
| Max. mounting height | 5 m |
| Light measurement | mixed light |
| Level of brightness | 3 - 1000 lx |
| Number of light channels | 1 |
| Number of switching contacts | 2 |
| Push button input lighting | 1 |
| Push button input HVAC | false |
| Slave input | yes, via DALI |
| Fully automatic | yes |
| Semi-automatic | yes |
| constant lighting control | true |
| Switching delay from "dark to light" [s] | 300 s |
| Switching delay from "light to dark" [s] | 30 s |

CONTROL

| Channel 1 | Lighting |
|--|---|
| Interface | Switching/Dimming |
| Contact | Bus system |
| Switch-off delay time | disabled/approx. $1 \text{ minute} - 240 \text{ minutes}$ |
| Orientation light | 10 % to 50 % luminous efficiency |
| Switch-off delay time, orientation light | disabled/approx. $1 \text{ minute} - 240 \text{ minutes}$ |
| Orientation light | 10 % to 50 % luminous efficiency |
| Switch-off delay time, orientation light | disabled/approx. 1 minute — 240 minutes |
| Bus voltage | 9.5–22.5 V DC |

DATA SHEET



PD-FLAT 360i/8 ROUND WHITE DALI SET


Order description Item number GTIN


PD-FLAT-S 360i/8 RW DALI EP10428708 4015120428708

| Master/slave function | true | |
|---------------------------|------|--|
| constant lighting control | true | |

| Manual override | yes, via IR |
|-----------------|----------------------|
| DALI output 1 | DALI bus / Broadcast |

Scale drawing Field of detections





■ Operating area approx. Ø 4 m ■ Head-on to detector approx. Ø 6 m ■ Passage area / diagonally to detector approx. Ø 8 m

Circuit diagram Circuit diagram

Standard operation

Master/Slave mode