

S09-



1 NO contact 16A/230V AC

Modular devices for DIN 60715 TH35 rail mounting with manual control and switch position indicator. Only ½ module = 9mm wide, 55mm deep. Control power demand 5W. For impulse control. Contact gap 3mm.

S09-230V

Technical data page 19-7.


S09-12V
S09-230V

1 NO 16A
1 NO 16A

EAN 4010312104187
EAN 4010312104200

23,00 €/pc.
23,00 €/pc.

S12-400-/310-/220-



4-pole 16A/250V AC

Modular devices for DIN 60715 TH35 rail mounting with manual control and switch position indicator, for impulse control. 2 modules = 36mm wide, 55mm deep. Time on: **impulse control only**. Control power demand 12-15W. Contacts: 4 NO, 3 NO + 1 NC, 2 NO + 2 NC. Contact gap 3mm.

Devices for 25A XS12, page 19-5.

Retrofittable auxiliary contact KM12.

* **Non-standard control voltages:** 8, 12, 24, 42, 48, 60, 110V/50Hz or 110, 115, 127 and 220V/60Hz as well as 6, 8, 12, 24, 42, 48, 60, 110 and 220V DC.

S12-220-230V

Technical data page 19-7.

S12-400-230V
S12-400-*

4 NO 16A
4 NO 16A

EAN 4010312104484

43,10 €/pc.
49,60 €/pc.

S12-310-230V
S12-310-*

3 NO + 1 NC 16A
3 NO + 1 NC 16A

EAN 4010312100639

43,10 €/pc.
49,60 €/pc.

S12-220-230V
S12-220-*

2 NO + 2 NC 16A
2 NO + 2 NC 16A

EAN 4010312100592

43,10 €/pc.
49,60 €/pc.

KM12



Contact module, 1 NO contact and 1 NC contact 4A/250V AC

Retrofittable to the left of all impulse switches S12 and XS12 as well as switching relays and installation contactors R12 and XR12. ½ module = 9mm wide.

KM12

Auxiliary contact 1 NO + 1 NC, 4A

EAN 4010312901243

14,10 €/pc.