

## B<sup>1</sup> Prefix® system wings



### B<sup>1</sup> Prefix® system wing bracket set

- Facilitates attachment to the reinforcement
- Pre-fixing by means of B<sup>1</sup> Prefix® installation technology
- Can be used for the following articles:
  - B<sup>1</sup> device socket
  - B<sup>1</sup> device connection socket
  - B<sup>1</sup> large-conduit device connection socket
  - B<sup>1</sup> electronics socket
  - B<sup>1</sup> two-device connection socket
  - B<sup>1</sup> wall light connection socket
  - B<sup>1</sup> universal wall outlet
  - B<sup>1</sup> Prefix® adapter - Ø 20, Ø 25 and Ø 32 mm

<b>Order number:</b>	<b>1211-00</b>
EAN:	4013456551367
Length	103 mm
Width	49 mm
Depth	36 mm
For concrete coverings of	20 - 60 mm
Number of wings	2
Packaging inner/dispatch	1/175

The B<sup>1</sup> Prefix® system wing allows fast, easy fixing to the reinforcement. This means optimal installation on the opposing formwork side and for free-standing reinforcement, and also for sliding or travelling formwork constructions. All wall applications in the new B<sup>1</sup> range have slots for the locking of two Prefix® system wings. This ensures fast, easy installation on the opposing formwork side.

- Fast, easy installation on rebar without support element before front formwork placed against it
- Holding in place using the Prefix® installation technology leaves both hands free for securing with tying wire
- A pronounced corrugated profile and additional fixing opportunities for secure fixing using tie wires
- Combinable when using wall and ceiling transitions
- For installation in exposed concrete, pressed against the front formwork
- Suitable for 20 - 60 mm concrete covers

