

Tap-radio® humidity temperature sensor TF-FTSB55

Eltako



TF-FTSB55

Tap-radio® humidity temperature sensor

Wireless humidity temperature sensor pure white glossy for single mounting 80x80x17mm or mounting in the 55 mm switch system. With battery (lifetime 5 years). Smart Home sensor.

The wireless humidity/temperature sensor measures constantly the relative humidity between 0 and 100% ($\pm 5\%$) and the temperature between -20 and $+60^{\circ}\text{C}$ ($\pm 0.5^{\circ}\text{C}$).

It sends a data telegram within 2 minutes if changed in the Eltako building radio. If there is no change, a status telegram is sent every 10 minutes. This interval can be reduced to 1 and 5 minutes by plugging the jumper 'interval'.

Evaluation by actuator F2L14, the Smart Home central unit MiniSafe, SafeIV, TouchIV etc. with the Eltako Wireless Building app GFA4.

We recommend stainless-steel countersunk screws 2.9x25mm, DIN 7982 C, for screw connections. Both with rawl plugs 5x25mm and with 55mm switch boxes. Set of 2 stainless-steel countersunk screws 2,9x25mm and plugs 5x25mm are enclosed.



private series

TF-FTSB55

Wireless humidity temperature sensor

EAN 4010312318348

56,50 €/pc.