



Line-TCPRS1

Line-TCPRS1, RS-485/RS-232 to Ethernet/Wi-Fi converter (ModbusTCP/TCP/UDP)
Integrated web server and mobile app (MyConfig) for configuration,

Code: M62411.

Description

The **line-TCPRS1** is a gateway designed to convert an RS-485 or RS-232 physical environment to Ethernet and/or Wi-Fi. The device features a Web Server and the MyConfig app (Android) that uses Bluetooth® connectivity, from which the user can fully edit the configuration parameters of the device.

The device can be connected via the side bus to the devices of the line range, without the need to cable the communications bus, making it much easier to install. It also has RS-485 and RS-232 communication terminals so that it can be simultaneously connected to other devices not in the line range.

Application

- The device is for installation inside an electric panel or enclosure, with DIN rail mounting (IEC 60715).
- The line-TCPRS1 comes with DHCP enabled by default.
- Connect up to 8 devices on the line bus, and up to 32 devices on the RS-485 communications bus.



Line-TCPRS1

RS-485 / RS-232 to TCP/IP converter

Code: M62411.

Specifications

AC power supply

Installation category	CAT III 300V
Consumption	3,5 ... 7,5 VA
Frequency	50 ... 60 Hz
Nominal voltage	100 ... 264 V ~

DC power supply

Consumption	2 ... 2,5 W
Nominal voltage	100 ... 300 Vdc

Mechanical characteristics

Size (mm) width x height x depth	52.5 x 117.85 x 70 (mm)
Screw type	Flat, M2.5
Envelope	Self-extinguishing V0 plastic
Torque setting	≤ 0,4 Nm
Communications cable cross-section	2.5 mm ²
Cable gauge at power supply terminals	2.5 mm ²
Fastening	DIN rail (IEC 60715)
Weight (kg)	0,192

Environmental characteristics

Protection class	IP30, Front: IP40
Relative humidity (without condensation)	5 ... 95%
Storage temperature	-20 ... +70 °C
Operating temperature	-10 ... +50 °C

Communications

Type	RS-485 / RS-232 / Ethernet / WiFi / Bluetooth
Technology	Ethernet, WiFi, Bluetooth 4.2 + EDR, Bluetooth LE

Standards

Electrical safety, Maximum height (m)	2000
Electrical safety, Installation category	CAT III 300 V
Standards	UNE-EN 61010-1, UNE-EN 61000-6-2, UNE-EN 61000-6-4

User interface

LED	7 LED
-----	-------



Line-TCPRS1

RS-485 / RS-232 to TCP / IP converter

Code: M62411.

Line-TCPRS1

RS-485 to Ethernet or Wi-Fi converter

CODE	TYPE	Description
M62411.	Line-TCPRS1	RS-485 / RS-232 to Ethernet / Wi-Fi converter (ModbusTCP / TCP / UDP) Integrated web server and mobile app (MyConfig) for configuration

Line-TCPRS1: Power supply 100... 264 VAC / 100... 300 VDC



Line-TCPRS1

RS-485 / RS-232 to TCP / IP converter

Code: M62411.

Dimensions

