



## 600004 1LF

Cable reductions

MADE IN ITALY

### DRAWINGS

• 6000041 • 6 KB • CONFIDENTIAL DOCUMENT



#### GENERAL DESCRIPTION

Type of product (Family)	Accessories
Product name (Series)	Cable reductions
Number of wires/cables	1 single conductor
Colour	naturale

**i** Cannot be used with nut code 6002002CC/CE e 6000115KC/CE. Can be used with nut code 6002001CC/CE.

#### MECHANICAL CHARACTERISTICS

Protection against solid/water (IP)	IP67/IP68 (according to the type of product to be used with this accessory)
Corrosion resistance	Salt mist, 1.000 ore, 5% salt solutions, 35°C EN60068-2-11:2000, Test Ka (168h)

#### CABLE CHARACTERISTICS

Cable diameter min. - max.	6.5 mm - 7.5 mm <i>- For smaller cables please take the proper grommet.</i>
----------------------------	--

#### MATERIAL CHARACTERISTICS

Body	POM
Material properties	Halogen Free - Silicone Free
Operating temperature range	-40°C / +125°C

#### PACKAGING INFORMATION

Packaging method	non assembled
Quantity (product/bag)	200 products/sacchetto
Unit weight	0.25 gram/product
Box dimension	-