



Cable reductions



















### **GENERAL DESCRIPTION**

Type of product (Family)	Accessories
Product name (Series)	Cable reductions
Number of wires/cables	1 single conductor
Colour	Techno green
Dimension	$\Phi$ 12.0 mm (est.), $\Phi$ 7.0 mm (inner), 7.0 mm (thickness)

### MECHANICAL CHARACTERISTICS

Protection against solid/water (IP)	IP67/IP68 (according to the type of product to be used with this accessory)
Corrosion resistance	Salt mist, 1.000 ore, 5% salt solutions, 35°C EN60068-2-11:2000, Test Ka (168h)

## CABLE CHARACTERISTICS

Cable diameter min max.	7.0 mm - 9.5 mm • Nut tightened 2.5 Nm (The cable reduction is suggested to be used).
Cable diameter with reduction	5.0 mm - 7.5 mm (with accessory code 600041LF) 4.5 mm - 6.0 mm (with accessory code 600042LF) - Nut tightened 2.5 Nm.

# MATERIAL CHARACTERISTICS

Body	TPE
Material properties	Halogen Free - Silicone Free
Operating temperature range	-40°C/+125°C

#### **PACKAGING INFORMATION**

THE BUILDING HELDING TO THE	
Packaging method	non assembled
Quantity (product/bag)	200 products/sacchetto
Unit weight	0.56 gram/product
Box dimension	-