



6000087LF

Cable reductions

















GENERAL DESCRIPTION

| Type of product (Family) | Accessories |
|--------------------------|--------------------|
| Product name (Series) | Cable reductions |
| Number of wires/cables | 1 single conductor |
| Colour | naturale |
| | |

14.0 Tan be used only for connectors with outer cable 7.0 mm - 13.5 / 7.0 mm - 14.0 mm / 10.5 mm - 14.0 mm. Cannot be used with nut code 6000269CC/CE.

MECHANICAL CHARACTERISTICS

| Protection against solid/water (IP) | IP68 |
|-------------------------------------|---|
| Corrosion resistance | Salt mist, 1.000 ore, 5% salt solutions, 35°C EN60068-2-11:2000, Test Ka (168h) |

CABLE CHARACTERISTICS

| Cable diameter min max. | 6.0 mm - 7.0 mm |
|-------------------------|--|
| | For smaller cables please take the proper grommet. |

MATERIAL CHARACTERISTICS

| Body | POM |
|-----------------------------|------------------------------|
| Material properties | Halogen Free - Silicone Free |
| Operating temperature range | -40°C/+125°C |

PACKAGING INFORMATION

| Packaging method | non assembled |
|------------------------|------------------------|
| Quantity (product/bag) | 200 products/sacchetto |
| Unit weight | 0.5 gram/product |
| Box dimension | - |

DRAWINGS

• 6000087LF

• 5 KB • 🔒 CONFIDENTIAL DOCUMENT