



NEXT AVAILABILITY

GREY VERSION		EFDS.2/GR Cat. No. EFDS200GR	EFDS.2/15/GR Cat. No. EFDS210GR	EFDS.2/P/GR Cat. No. EFDS220GR
TECHNICAL CHARACTERISTICS				
Function / type		2 levels disconnect	2 levels disconnect	2 levels Feed-through
Rated cross-section	[mm ²]	2,5	2,5	2,5
Connecting capacity	Flexible [mm ²]	0,2 ÷ 4	0,2 ÷ 4	0,2 ÷ 4
	Rigid [mm ²]	0,2 ÷ 4	0,2 ÷ 4	0,2 ÷ 4
	Max. flexible with ferrule [mm ²]-ferrule type	2,5 - WP25/14	2,5 - WP25/14	2,5 - WP25/14
Electrical characteristics according to European standard IEC EN 60947-7-1	Maximum voltage AC/DC [V]	630	630	630
	Maximum current (with cable from 2,5mm ²) [A]	-	-	-
	Section Caliber	A3	A3	A3
Electrical characteristics according to UL standard	Maximum voltage AC/DC [V]	UL Pending	UL Pending	UL Pending
	Maximum current (with cable from 2,5mm ²) [A]	UL Pending	UL Pending	UL Pending
	Section Min-Max [AWG]	UL Pending	UL Pending	UL Pending
Rated impulse withstand voltage / pollution degree		8kV / 3	8kV / 3	8kV / 3
Insulation stripping length	[mm]	9	9	9
Wight	[mm]	5,2	5,2	5,2
Length	[mm]	110	110	110
Height mounted on TH35 / 15	[mm]	39,2	39,2	39,2
Height mounted on TH35 / 7,5	[mm]	54	54	54
Insulation material temperature index (EN 60216-1)	[°C]	130	130	130
Plastic material		Polyamide UL94 V0	Polyamide UL94 V0	Polyamide UL94 V0

APPROVALS

ACCESSORIES		TYPE	CAT. NO.	TYPE	CAT. NO.	TYPE	CAT. NO.
End section	grey	EFDS.2/PT/GR	EFDS201GR	EFDS.2/PT/GR	EFDS201GR	EFDS.2/PT/GR	EFDS201GR
	End section thickness [mm]	1,5		1,5		1,5	
"Easy Bridge" (PTC) cross connection	2 poles	EFB.2/2/R	EFB0202R	EFB.2/2/R	EFB0202R	EFB.2/2/R	EFB0202R
	3 poles	EFB.2/3/R	EFB0203R	EFB.2/3/R	EFB0203R	EFB.2/3/R	EFB0203R
	5 poles	EFB.2/5/R	EFB0205R	EFB.2/5/R	EFB0205R	EFB.2/5/R	EFB0205R
	10 poles	EFB.2/10/R	EFB0210R	EFB.2/10/R	EFB0210R	EFB.2/10/R	EFB0210R
105mm adhesive numbering strip (20 terminal blocks)		TAM10105AW	TAM10105AW	TAM10105AW	TAM10105AW	TAM10105AW	TAM10105AW
Single marking tag		CNU/10/51	NU1051S	CNU/10/51	NU1051S	CNU/10/51	NU1051S
Single marking tag for pitch insert		CNU/10/51	NU1051S	CNU/10/51	NU1051S	CNU/10/51	NU1051S
End bracket	Screw	BT/3	BT003	BT/3	BT003	BT/3	BT003
	Snap-fit	BTO	BT007	BTO	BT007	BTO	BT007