

POS switchable cross connections



If the linking of adjacent terminal blocks is occasional, a **POS** switchable cross connection may be used; it consists of:

- 2 screws
- 2 sleeves
- 1 linking plate with open slot, allowing easy opening and closing of the cross connection.

Terminal block	Cross connection		Screw M x l (mm)	Sleeve Ø x l (mm)
	Type	Cat. No.		
CBC.16	POS/53	POS53	4 x 35	5,1 x 30
CBD.2	POS/11	POS11	2,5 x 22	4 x 18
CBD.4	POS/42	POS42	3 x 28	4 x 23
CBD.6	POS/93	POS93	3,5 x 27	5,5 x 21,5
CBD.10	POS/44	POS44	4 x 25	5,5 x 21,5
CBD.16	POS/44	POS44	4 x 25	5,5 x 21,5
CBD.35	POS/66	POS66	4 x 30	8 x 22
CBD.50	POS/07	POS07	5 x 30	8 x 23,5
CBD.70	POS/08	POS08	5 x 40	8 x 30
DAS.4	POS/43	POS43	3 x 20	4 x 16
EDM.2	POS/11	POS11	2,5 x 22	4 x 18
EDM.4	POS/42	POS42	3 x 28	4 x 23
EDM.6	POS/93	POS93	3,5 x 27	5,5 x 21,5
EDM.10	POS/44	POS44	4 x 25	5,5 x 21,5
EDM.16	POS/44	POS44	4 x 25	5,5 x 21,5
EDM.25	POS/66	POS66	4 x 30	8 x 22
EDM.35	POS/07	POS07	5 x 30	8 x 23,5
EDM.70	POS/08	POS08	5 x 40	8 x 30
FFS.4	POS/72	POS72	3 x 20	4 x 14,5
FVS.4	POS/72	POS72	3 x 20	4 x 14,5
MPS.2/SV-SW-SWP	POS/91	POS91	2,5 x 25	4 x 20
SV.2	POS/11	POS11	2,5 x 22	4 x 18
SV.4	POS/12	POS12	3 x 22	4 x 18
SV.6	POS/13	POS13	3 x 30	5,5 x 25
SV.10	POS/14	POS14	3,5 x 30	5,5 x 25
TLD.2	POS/41	POS41	2,5 x 16	4 x 12,7
TLS.2	POS/41	POS41	2,5 x 16	4 x 12,7
RP.4	POS/43	POS43	3 x 20	4 x 16