

Plug-in jumper for CK series

Notes:

- (1) Example of a pre-cut 9 position jumper
- (2) CK/PT end section must be mounted on last module to assure IP20 protection degree
- (3) 32 A is the maximum current; however this value is limited by the rated current of the spring-clamp terminal blocks down to 24 A; for instance, having a jumper of 11 poles (1 for common and 10 for distribution) a current of 2.4 A can be distributed on every poles



VERSIONS	Item	Cat. No.
	PTC/CK/42	PTCCK42
GENERAL TECHNICAL DATA		
Protection degree (2)	IP20 IEC529; EN60529	
Number of poles	42	
Pitch	6 mm (0.24 in)	
Rated current carrying capacity of jumper (3)	32 A	
Insulation color	—	
Material	tin copper alloy	
Approx. weight	27 g (0.95 oz) (42 poles)	

Plug-in jumper for CW..7 series



VERSIONS	Item	Cat. No.	Item	Cat. No.	Item	Cat. No.
	CWBK 7-0802	X766802	CWBK 7-0803	X766803	CWBK 7-0804	X766804
GENERAL TECHNICAL DATA						
Protection degree	IP20 IEC529; EN60529		IP20 IEC529; EN60529		IP20 IEC529; EN60529	
Number of poles	16		16		16	
Pitch	6.2 mm (2.44 in)		6.2 mm (2.44 in)		6.2 mm (2.44 in)	
Rated current carrying capacity of jumper	16 A		16 A		16 A	
Insulation color	red		white		blue	
Material	—		—		—	
Approx. weight	4 g (0.14 oz)		4 g (0.14 oz)		4 g (0.14 oz)	

Plug-in jumper for CWRE series



VERSIONS	Item	Cat. No.
	CWBK 7-0813	X766813
GENERAL TECHNICAL DATA		
Protection degree	IP20 IEC529; EN60529	
Number of poles	20	
Pitch	6.2 mm (2.44 in)	
Rated current carrying capacity of jumper	16 A	
Insulation color	blue	
Material	—	
Approx. weight	6 g (0.21 oz)	