

## **PZM protection covers and PZD supports**


Terminal blocks having a cross-section up to 70 mm<sup>2</sup> can be protected against accidental contacts or tampering, by means of a **PVC** transparent cover, **supplied in a standard lenght of 2 m**, to be mounted on appropriate polyamide supports and to be inserted on PR/DIN, PR/3, "G32" type and TH/35.mounting rails.

They can be fixed by sealing the support ends.

## **PZM.4 cover** (a = 64+2 mm / b = 32 mm) Cat. No. **PZ330**

Suitable for terminal blocks with **overall dimension up to approximately 58 mm** (mounting rail included). To be mounted with **PZD.4/SO** supports (Cat. No. PZ331) Maximum dimension PZM.4 + PZD.4/SO - on IEC 60715/G32 mounting rail = 70 or 82 mm (\*) - on IEC 60715/TH35 mounting rail = 65 or 77 mm (\*)

(\*) depending on the notches used, upper or lower.



PZM.4 - PZM.6 covers

## **PZM.6 cover** (a = 85+2 mm / b = 36 mm) Cat. No. **PZ110**


Suitable for terminal blocks with **overall dimension over 58 mm,** (mounting rail included).

To be mounted with **PZD.6/S0** supports (Cat. No.PZ112) Maximum dimension PZM.6 + PZD.6/S0

- on IEC 60715/G32 mounting rail = 82 o 94 mm (\*)

- on IEC 60715/TH35 mounting rail = 78 o 90 mm (\*)

(\*) depending on the notches used, upper or lower.




PZD.4/SO - PZD.6/SO supports

## **PRP** protections

The cross connection, consisting of a PMP multiple commoning bar and CPM screws and sleeves, already placed in a recessed position with respect to the terminal board, can be further protected from accidental contact using a nylon U-shaped cover having a standard length of 10 cm. This white-coloured cover, can also be written upon, to serve as a label or reference point on the terminal board.

On the cover suitable slits are arranged to facilitate its removal by using a screwdriver.

for terminal blocks with a cross section of 2,5-4 mm <sup>2</sup>	PRP/6	Cat. No. <b>PRP06</b>
for terminal blocks with a cross section of 4-16 $\mbox{mm}^2$	PRP/7	Cat. No. <b>PRP07</b>
for terminal blocks with a cross section of 25-70 mm <sup>2</sup>	PRP/8	Cat. No. <b>PRP08</b>
for terminal blocks type TLD.2-TLS.2-CBR.2- DAS.4-TLE.2-TDE.2	PRP/5 (red, blue, white)	Cat. No. <b>PRP05</b>



PRP protections