


## Cable glands Progress® nickel-plated brass



### Short entry thread metric

#### Type approval: Progress MS

- One-piece sealing insert
- not overall length insulated

|                                    |                              |
|------------------------------------|------------------------------|
| <b>Order number:</b>               | <b>1000.63.400</b>           |
| E-No:                              | 121079938                    |
| EAN:                               | 7611614104485                |
| Material                           | Nickel-plated brass          |
| Seal                               | TPE / NBR                    |
| O-ring                             | NBR                          |
| Operation temperature              | -40°C / +100°C               |
| Strain relief                      | Version A acc. to EN 62444   |
| Protection class                   | IP 68 (up to 10 bar) / IP 69 |
| NEMA Type rating                   | 4X                           |
| Entry thread                       | M63x1.5                      |
| Clamping range without insert min. | 35.0 mm                      |
| Clamping range without insert max. | 40.0 mm                      |
| Wrench size                        | 70 mm                        |
| Dimension H                        | 37 mm                        |
| Thread length L                    | 10 mm                        |
| UL - clamping range                | 35.0-40.0 mm                 |
| Dispatch                           | 5                            |

1 = Metric coarse-pitch thread (with VDE test report)

Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.