


Cable glands Progress® EMC nickel-plated brass with antikink spring



Short entry thread metric

Type approval: Progress MS EMV FKN

- One-piece sealing insert
- not overall length insulated

| | |
|------------------------------------|--|
| Order number: | 1080.10.52.040 |
| E-No: | 121782208 |
| EAN: | 7611614195520 |
| Material | Nickel-plated brass |
| Antikink spring | Stainless steel A2 |
| Seal | TPE |
| O-ring | NBR |
| Operation temperature | -40°C / +100°C |
| Strain relief | Version A acc. to EN 62444 |
| Protection class | IP 68 (up to 10 bar) / IP 69 |
| Properties | Excellent shield contact through the contact sleeve with the braided shield terminating in the screwed cable gland |
| Entry thread | M10x1.5 |
| Clamping range without insert min. | 3.0 mm |
| Clamping range without insert max. | 4.0 mm |
| Wrench size | 13 mm |
| Dimension H | 54 mm |
| Thread length L | 5 mm |
| Note | 1 |
| Dispatch | 10 |

1 = Metric coarse-pitch thread (with VDE test report)

Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.

Available on request:

- Long entry thread