

## Cable glands Progress® EMC nickel-plated brass with contact sleeve



### Short entry thread metric

#### Type approval: Progress MS EMV

- One-piece sealing insert
- not overall length insulated

|                                    |  |
|------------------------------------|--|
| <b>Order number:</b>               | <b>1080.17.100</b>   |
| E-No:                              | 121072318  |
| EAN:                               | 7611614114811  |
| Material                           | Nickel-plated brass  |
| Contact sleeve                     | Nickel-plated brass  |
| Seal                               | TPE  |
| O-ring                             | NBR  |
| Operation temperature              | -40°C / +100°C   |
| Strain relief                      | Version A acc. to EN 62444   |
| Protection class                   | IP 68 (up to 10 bar) / IP 69   |
| NEMA Type rating                   | 4X   |
| Properties                         | Excellent shield contact through the contact sleeve with the braided shield terminating in the screwed cable gland |
| Entry thread                       | M16x1.5  |
| Clamping range without insert min. | 8.0 mm   |
| Clamping range without insert max. | 10.0 mm  |
| Wrench size                        | 18 mm  |
| Dimension H                        | 25 mm  |
| Thread length L                    | 5 mm   |
| Dispatch                           | 50   |

1 = Metric coarse-pitch thread (with VDE test report)

Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.