

## Cable glands Progress® EMC Rapid nickel-plated brass with contact disc



### Short entry thread metric

#### Type approval: Progress MS EMV Rapid

- One-piece sealing insert
- not overall length insulated

|                                    |   |
|------------------------------------|---|
| <b>Order number:</b>               | <b>1081.12.060</b>  |
| E-No:                              | 121072228   |
| EAN:                               | 7611614207001   |
| Material                           | Nickel-plated brass   |
| Contact sleeve                     | Nickel-plated brass   |
| Contact disc                       | Stainless steel A2  |
| Seal                               | TPE   |
| O-ring                             | NBR   |
| Operation temperature              | -40°C / +100°C  |
| Strain relief                      | Version A acc. to EN 62444  |
| Protection class                   | IP 68 (up to 10 bar) / IP 69  |
| NEMA Type rating                   | 4X  |
| Properties                         | For a quick installation of partially dismantled cables as well as thoroughly shielded cables |
| Entry thread                       | M12x1.5   |
| Clamping range without insert min. | 4.5 mm  |
| Clamping range without insert max. | 6.0 mm  |
| Wrench size                        | 15 mm   |
| Dimension H                        | 20 mm   |
| Thread length L                    | 5 mm  |
| Dispatch                           | 50  |

