


## Cable glands Progress® EMC powerCONNECT nickel-plated brass



### Long entry thread metric

#### Type approval: Progress EMV powerCONNECT

- Two-piece sealing insert
- not overall length insulated

|                                    |   |
|------------------------------------|---|
| <b>Order number:</b>               | <b>1184.17</b>  |
| E-No:                              | 121082308   |
| EAN:                               | 7611614312675   |
| Material                           | Nickel-plated brass   |
| Seal                               | TPE   |
| O-ring                             | NBR   |
| Operation temperature              | -60°C / +100°C  |
| Strain relief                      | Version A acc. to EN 62444  |
| Protection class                   | IP 68 (up to 10 bar) / IP 69  |
| NEMA Type rating                   | 4X  |
| Properties                         | For high leakage currents, concentric 360° shield contact ensure extremely low transfer resistance and transfer impedance. Compact design |
| Entry thread                       | M16x1.5   |
| Clamping range with insert min.    | 6.0 mm  |
| Clamping range with insert max.    | 8.0 mm  |
| Clamping range without insert min. | 8.0 mm  |
| Clamping range without insert max. | 10.5 mm   |
| Cable shield diameter              | 9.3   |
| Inner diameter                     | 8.2 mm  |
| Wrench size                        | 18 mm   |
| Dimension H                        | 28 mm   |
| Thread length L                    | 10 mm   |
| Additional note                    | -   |
| Dispatch                           | 25  |

1 = One-piece sealing insert

Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.

#### Available on request:

- Stainless steel A2 or A4
- Entry thread Pg and NPT