


Cable glands Progress® EMC powerCONNECT nickel-plated brass



Long entry thread metric

Type approval: Progress EMV powerCONNECT

- Two-piece sealing insert
- not overall length insulated

| | |
|------------------------------------|---|
| Order number: | 1184.63 |
| E-No: | 121082948 |
| EAN: | 7611614312613 |
| Material | Nickel-plated brass |
| Seal | TPE |
| O-ring | NBR |
| Operation temperature | -60°C / +100°C |
| Strain relief | Version A acc. to EN 62444 |
| Protection class | IP 68 (up to 10 bar) / IP 69 |
| NEMA Type rating | 4X |
| Properties | For high leakage currents, concentric 360° shield contact ensure extremely low transfer resistance and transfer impedance. Compact design |
| Entry thread | M63x1.5 |
| Clamping range with insert min. | 40.0 mm |
| Clamping range with insert max. | 46.0 mm |
| Clamping range without insert min. | 46.0 mm |
| Clamping range without insert max. | 52.0 mm |
| Cable shield diameter | 48.6 |
| Inner diameter | 46.6 mm |
| Wrench size | 70 mm |
| Dimension H | 49 mm |
| Thread length L | 14 mm |
| Additional note | - |
| Dispatch | 5 |

1 = One-piece sealing insert

Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.

Available on request:

- Stainless steel A2 or A4
- Entry thread Pg and NPT