

## Short entry thread Pg



**AGRO**

## AGRO combination conduit glands Progress® nickel-plated brass with integrated cable gland

### Type approval: Progress MS Kombi

- Connector for tubing with AD mm
- Two-piece sealing insert
- not overall length insulated

|                                    |   |
|------------------------------------|---|
| <b>Order number:</b>               | <b>1700.48.56</b>   |
| EAN:                               | 7611614144115   |
| Material                           | Nickel-plated brass   |
| Seal                               | TPE   |
| O-ring                             | NBR   |
| Operation temperature              | -40°C / +100°C  |
| Protection class                   | Cable gland IP 68   |
| Note                               | The max. clamping range depends on the conduit inner diameter |
| Entry thread                       | Pg 48   |
| Outer diameter                     | 56 mm   |
| Clamping range with insert min.    | 37.0 mm   |
| Clamping range with insert max.    | 43.0 mm   |
| Clamping range without insert min. | 43.0 mm   |
| Clamping range without insert max. | 49.0 mm   |
| Wrench size                        | 65/66 mm  |
| Dimension H                        | 67 mm   |
| Thread length L                    | 11 mm   |
| Dispatch                           | 10  |

Depending on the type of conduit, the stabilising bush must be ordered separately. Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.