

AGRO Ex cable glands nickel-plated brass for flameproof enclosure Ex d IIC



Entry thread Pg

Type approval: Serie 18

- One-piece sealing insert
- not overall length insulated

| | |
|------------------------------------|---|
| Order number: | 1836.26 |
| E-No: | 121440708 |
| EAN: | 7611614040981 |
| Material | Nickel-plated brass |
| Screws | Stainless steel A2 |
| Seal | NBR |
| O-ring | FPM |
| Operation temperature | -40°C / +100°C |
| Protection class | IP 68 (30 bar) |
| Test standard | IEC EN 60079-0 / IEC EN 60079-1 / IEC EN 60079-31 |
| Gas | II 2G Ex db eb IIC |
| Dust | II 2D Ex ta IIIC |
| Zone | Gas 1 and 2 / dust 21 and 22 |
| Certificate | PTB 00 ATEX 1059 |
| IECEx Certificate | IECEx PTB 12.0056 |
| Entry thread | Pg 36 |
| Clamping range without insert min. | 28.0 mm |
| Clamping range without insert max. | 32.0 mm |
| Wrench size | 55 mm |
| Diameter A | 60 |
| Dimension H | 85 mm |
| Thread length L | 17 mm |
| Dispatch | 5 |