

**AGRO Kabelverschraubungen Ex Compact Messing mit Klemmbacken Ex d IIC und Ex e II**


**AGRO cable glands Ex Compact nickel-plated brass with clamps Ex d IIC and Ex e II**

Material: Messing vernickelt  
 Dichtung: NBR  
 O-Ring: FPM  
 Einsatztemperatur: -60°C / +105°C  
 Schutzart: IP 68 (30 bar)  
 Prüfnorm: IEC EN 60079-0 / IEC EN 60079-1 / IEC EN 60079-7 / IEC EN 60079-31

Material: Nickel-plated brass  
 Seal: NBR  
 O-ring: FPM  
 Temperature range: -60°C / +105°C  
 Protection class: IP 68 (30 bar)  
 Test standard: IEC EN 60079-0 / IEC EN 60079-1 / IEC EN 60079-7 / IEC EN 60079-31

Gas: II 2G Ex db eb IIC Gb  
 Staub: II 2D Ex tb IIIC Db  
 Zone: Gas 1 und 2 / Staub 21 und 22  
 Zertifikat: SEV 17 ATEX 0153  
 IECEx Zertifikat: IECEx SEV 17.0017

Gas: II 2G Ex db eb IIC Gb  
 Dust: II 2D Ex tb IIIC Db  
 Zone: Gas 1 and 2 / dust 21 and 22  
 Certificate: SEV 17 ATEX 0153  
 IECEx Certificate: IECEx SEV 17.0017



**EX Compact MS KB**



Einteiliger Dichteinsatz  
 nicht durchgehend isolierend

One-piece sealing insert  
 not overall length insulated

G	>Ø< min mm	>Ø< max mm	Ø mm	H mm	L mm	Art.-Nr.   Art. No.	
M16x1.5	3.0	7.0	21	34	12	EX1826.17.070	25
M16x1.5	5.0	10.0	24	35	12	EX1826.17.100	25
M20x1.5	5.0	11.0	24	35	12	EX1826.20.110	25
M20x1.5	9.0	14.0	30	35	12	EX1826.20.140	25
M25x1.5	7.5	15.0	32	37	12	EX1826.25.150	20
M25x1.5	12.5	18.0	32	37	12	EX1826.25.180	20
M32x1.5	17.0	23.0	41	42	12	EX1826.32.230	10
M32x1.5	21.0	26.0	41	42	12	EX1826.32.260	10
M40x1.5	21.0	26.0	41	42	14	EX1826.40.260	10
M40x1.5	24.0	32.0	50	47	14	EX1826.40.320	10
M50x1.5	28.0	36.0	55	48	14	EX1826.50.360	5
M50x1.5	35.0	42.0	60	50	14	EX1826.50.420	5
M63x1.5	36.0	44.0	65	51	14	EX1826.63.440	1
M63x1.5	43.0	50.0	70	51	14	EX1826.63.500	1

Auf Anfrage lieferbar:  
 Anschlussgewinde Pg und NPT  
 Rostfreier Stahl A2 oder A4

Available on request:  
 Entry thread Pg and NPT  
 Stainless steel A2 or A4

