

AGRO cable glands Progress® nickel-plated brass increased safety Ex e II for



Short entry thread metric

Type approval: Progress MS Multi EX

- One-piece sealing insert
- not overall length insulated

| | |
|------------------------------------|---|
| Order number: | EX1310.32.4.090 |
| EAN: | 7611614239347 |
| Material | Nickel-plated brass |
| Seal | TPE / NBR |
| O-ring | FPM |
| Operation temperature | -60°C / +100°C |
| Protection class | IP 66 / IP 68 |
| Test standard | IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31 |
| Gas | II 2G Ex eb IIC Gb |
| Dust | II 2D Ex tb IIIC Db |
| Zone | Gas 1 and 2 / dust 21 and 22 |
| Certificate | SEV 15 ATEX 0152X |
| IECEX Certificate | IECEX SEV 15.0019X |
| Entry thread | M32x1.5 |
| Clamping range without insert min. | 7.5 mm |
| Clamping range without insert max. | 9.0 mm |
| Number of cables | 4 |
| Wrench size | 36 mm |
| Dimension H | 28 mm |
| Dimension L | 8 mm |
| Dispatch | 25 |

3 = Material sealing insert NBR
 Suitable locking pins see accessories

Available on request:

- Executions in steel A2 and A4, entry thread NPT