


AGRO synthetic cable glands Progress® GFK for increased safety Ex e II with



Entry thread metric

Type approval: Progress GFK Multi EX

- Black RAL 9005
- One-piece sealing insert

| | |
|------------------------------------|---|
| Order number: | EX1540.25.6.060 |
| EAN: | 7611614239712 |
| Material | Polyamide glass fiber reinforced |
| Properties | halogen-free |
| Seal | TPE / NBR |
| Operation temperature | -20°C / +85°C |
| Protection class | IP 66 / IP 68 |
| Test standard | IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31 |
| Gas | II 2G Ex eb IIC Gb |
| Dust | II 2D Ex tb IIIC Db |
| Zone | Gas 1 and 2 / dust 21 and 22 |
| Certificate | SEV 15 ATEX 0152X |
| IECEX Certificate | IECEX SEV 15.0019X |
| Entry thread | M25x1.5 |
| Clamping range without insert min. | 5.0 mm |
| Clamping range without insert max. | 6.0 mm |
| Number of cables | 6 |
| Wrench size | 34 mm |
| Dimension H | 33 mm |
| Dimension L | 13 mm |
| Dispatch | 25 |

3 = Material sealing insert NBR
 Suitable locking pins see accessories