


# AGRO synthetic cable glands Progress® GFK for increased safety Ex e II with



## Entry thread Pg

### Type approval: Progress GFK Multi EX

- Black RAL 9005
- One-piece sealing insert

|                                    |   |
|------------------------------------|---|
| <b>Order number:</b>               | <b>EX1540.36.2.150</b>                            |
| EAN:                               | 7611614240930                                     |
| Material                           | Polyamide glass fiber reinforced                  |
| Properties                         | halogen-free                                      |
| Seal                               | TPE / NBR   |
| Operation temperature              | -20°C / +85°C                                     |
| Protection class                   | IP 66 / IP 68                                     |
| Test standard                      | IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31 |
| Gas                                | II 2G Ex eb IIC Gb                                |
| Dust                               | II 2D Ex tb IIIC Db                               |
| Zone                               | Gas 1 and 2 / dust 21 and 22                      |
| Certificate                        | SEV 15 ATEX 0152X                                 |
| IECEX Certificate                  | IECEX SEV 15.0019X                                |
| Entry thread                       | Pg 36   |
| Clamping range without insert min. | 14.0 mm   |
| Clamping range without insert max. | 15.0 mm   |
| Number of cables                   | 2   |
| Wrench size                        | 55 mm   |
| Dimension H                        | 42 mm   |
| Dimension L                        | 16 mm   |
| Note                               | 3   |
| Dispatch                           | 10  |

3 = Material sealing insert NBR