

## AGRO synthetic cable glands Progress® GFK increased safety Ex e II



### Entry thread metric

#### Type approval: Progress GFK EX

- Light grey RAL 7035
- One-piece sealing insert

|                                    |   |
|------------------------------------|---|
| <b>Order number:</b>               | <b>EX1571.32.255</b>                              |
| E-No:                              | 121760738   |
| EAN:                               | 7611614175867                                     |
| Material                           | Polyamide glass fiber reinforced                  |
| Properties                         | halogen-free                                      |
| Seal                               | TPE / NBR   |
| Operation temperature              | -20°C / +85°C                                     |
| Protection class                   | IP 66 / IP 68                                     |
| Test standard                      | IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31 |
| Gas                                | II 2G Ex eb IIC Gb                                |
| Dust                               | II 2D Ex tb IIC Db                                |
| Zone                               | Gas 1 and 2 / dust 21 and 22                      |
| Certificate                        | SEV 15 ATEX 0152X                                 |
| IECEx Certificate                  | IECEx SEV 15.0019X                                |
| Entry thread                       | M32x1.5   |
| Clamping range without insert min. | 23.0 mm   |
| Clamping range without insert max. | 25.5 mm   |
| Wrench size                        | 41 mm   |
| Dimension H                        | 35 mm   |
| Thread length L                    | 15 mm   |
| Dispatch                           | 25  |

3 = Material sealing insert NBR