

## AGRO EMC cable glands Progress® nickel-plated brass with contact sleeve and

**Short entry thread Pg****Type approval: Progress MS EMC KB EX**

- One-piece sealing insert
- not overall length insulated

|                                    |   |
|------------------------------------|---|
| <b>Order number:</b>               | <b>EX1803.80.07.075</b>                           |
| EAN:                               | 7611614176819                                     |
| Material                           | Nickel-plated brass                               |
| Screws                             | Stainless steel A2                                |
| Seal                               | TPE   |
| O-ring                             | FPM   |
| Operation temperature              | -60°C / +100°C                                    |
| Protection class                   | IP 66 / IP 68 (up to 10 bar)                      |
| Test standard                      | IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31 |
| Gas                                | II 2G Ex eb IIC Gb                                |
| Dust                               | II 2D Ex tb IIIC Db                               |
| Zone                               | Gas 1 and 2 / dust 21 and 22                      |
| Certificate                        | SEV 15 ATEX 0151                                  |
| IECEx Certificate                  | IECEx SEV 15.0018                                 |
| Entry thread                       | Pg 7  |
| Clamping range without insert min. | 6.0 mm  |
| Clamping range without insert max. | 7.5 mm  |
| Wrench size                        | 15/16 mm  |
| Dimension H                        | 26 mm   |
| Thread length L                    | 6 mm  |
| Note                               | 1   |
| Dispatch                           | 50  |

1 = Certificate SEV 15 ATEX 0152X / IECEx SEV 15.0019X\_x000D\_  
Long entry thread available on request