

AGRO EMC cable glands Progress® nickel-plated brass with contact sleeve and



Short entry thread metric

Type approval: Progress MS EMC KB EX

- One-piece sealing insert
- not overall length insulated

| | |
|------------------------------------|---|
| Order number: | EX1803.80.40.285 |
| E-No: | 121392808 |
| EAN: | 7611614177359 |
| Material | Nickel-plated brass |
| Screws | Stainless steel A2 |
| Seal | TPE |
| O-ring | FPM |
| Operation temperature | -60°C / +100°C |
| Protection class | IP 66 / IP 68 (up to 10 bar) |
| Test standard | IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31 |
| Gas | II 2G Ex eb IIC Gb |
| Dust | II 2D Ex tb IIIC Db |
| Zone | Gas 1 and 2 / dust 21 and 22 |
| Certificate | SEV 15 ATEX 0151 |
| IECEx Certificate | IECEx SEV 15.0018 |
| Entry thread | M40x1.5 |
| Clamping range without insert min. | 24.0 mm |
| Clamping range without insert max. | 28.5 mm |
| Wrench size | 46 mm |
| Dimension H | 44 mm |
| Thread length L | 8 mm |
| Note | - |
| Dispatch | 10 |

1 = Certificate SEV 15 ATEX 0152X / IECEx SEV 15.0019X_x000D_
Long entry thread available on request