


## AGRO cable glands Progress® nickel-plated brass with trumpet and clamps in



### Long entry thread metric

#### Type approval: Progress MS T+KB EX

- Two-piece sealing insert
- not overall length insulated

|                                    |   |
|------------------------------------|---|
| <b>Order number:</b>               | <b>EX1811.40</b>                                  |
| E-No:                              | 121446808   |
| EAN:                               | 7611614176659                                     |
| Material                           | Nickel-plated brass                               |
| Screws                             | Stainless steel A2                                |
| Seal                               | TPE   |
| O-ring                             | FPM   |
| Operation temperature              | -60°C / +100°C                                    |
| Protection class                   | IP 66 / IP 68 (up to 10 bar)                      |
| Test standard                      | IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31 |
| Gas                                | II 2G Ex eb IIC Gb                                |
| Dust                               | II 2D Ex tb IIIC Db                               |
| Zone                               | Gas 1 and 2 / dust 21 and 22                      |
| Certificate                        | SEV 15 ATEX 0151                                  |
| IECEx Certificate                  | IECEx SEV 15.0018                                 |
| Entry thread                       | M40x1.5   |
| Clamping range with insert min.    | 24.0 mm   |
| Clamping range with insert max.    | 28.5 mm   |
| Clamping range without insert min. | 28.5 mm   |
| Clamping range without insert max. | 33.0 mm   |
| Wrench size                        | 46 mm   |
| Diameter A                         | 57  |
| Dimension H                        | 59 mm   |
| Thread length L                    | 13 mm   |
| Dispatch                           | 5   |