


AGRO cable glands Ex Compact nickel-plated brass with clamps Ex d IIC and



Entry thread metric

Type approval: EX Compact MS KB

- One-piece sealing insert
- not overall length insulated

| | |
|------------------------------------|--|
| Order number: | EX1826.40.320 |
| E-No: | 121472758 |
| EAN: | 7611614316192 |
| Material | Nickel-plated brass |
| Seal | NBR |
| O-ring | FPM |
| Operation temperature | -60°C / +105°C |
| Protection class | IP 66 / IP 68 (30 bar) |
| Test standard | IEC EN 60079-0 / IEC EN 60079-1 / IEC EN 60079-7 / IEC EN 60079-31 |
| Gas | II 2G Ex db eb IIC Gb |
| Dust | II 2D Ex tb IIIC Db |
| Zone | Gas 1 and 2 / dust 21 and 22 |
| Certificate | SEV 17 ATEX 0153 |
| IECEx Certificate | IECEx SEV 17.0017 |
| Entry thread | M40x1.5 |
| Clamping range without insert min. | 24.0 mm |
| Clamping range without insert max. | 32.0 mm |
| Wrench size | 50 mm |
| Dimension H | 47 mm |
| Thread length L | 14 mm |
| Dispatch | 10 |

Available on request:

- Entry thread Pg and NPT
- Stainless steel A2 or A4