



THR.370.B2A

TH370 - mini plug&socket connector with insulation piercing system IP68

MADE IN ITALY



PIERCING KIT



INSTALLATION INSTRUCTIONS

- 606002028 IST TH370 PDF • 917 KB

CERTIFICATIONS AND TEST REPORTS

- CE-TH370 DOC • 203 KB
- TH370 Nemko EN60998 PDF • 670 KB
- TH370 Nemko EN60529 PDF • 466 KB

GENERAL DESCRIPTION

Type of installation	Plug and Socket connector
Type of product (Family)	TEEPLUG® - IP68 Plug&Socket circular connectors
Product name (Series)	TH370 - mini plug&socket connector with insulation piercing system IP68
Product configuration	Insulation piercing socket connector <i>• Plug&Socket connectors included in the kit. Accessories included in the kit.</i>
Type of Fixation	With quick-fix mounting clip <i>• Mounting clip to be ordered separately (code 6000302CC).</i>
Colour	Black (Plastic components) - Techno green (Rubber components)
Outer dimension	Φ 32 mm x 44 mm x 130 mm (when plug-socket matched)

ELECTRICAL CHARACTERISTICS

Number of poles	2
Contact marking	L - N
Type of connection	insulation piercing screw (M3 - max. 1.0 Nm) <i>• The piercing solution is ideal for PVC, Neoprene and FEP cables.</i>
Operating current	max. 17.5A
Operating voltage	max. 400V AC
Impulse withstand voltage	4KV

i Contact our Customer Service for availability of other markings. The connector can be used for Classe 2 devices up to 250V AC (EN60598-1:2008-10).

MECHANICAL CHARACTERISTICS

Protection against solid/water (IP)	IP65/IP68
Corrosion resistance	Salt mist, 1.000 ore, 5% salt solutions, 35°C EN60068-2-11:2000, Test Ka (168h)

i Contact our Customer Service for availability of products with different IP and IK protection degrees.

CABLE CHARACTERISTICS

Wire cross-section min. - max. (Stranded cable)	4.0 mm ² - 6.0 mm ² (main cable) 0.5 mm ² - 4.0 mm ² (branch cable) <i>• Warning: ensure that plug and socket are connected before piercing the main cable.</i>
Cable diameter min. - max.	7.0 mm - 8.0 mm (cavo main cable) / 5.0 mm - 12.0 mm (cavo branch cable) <i>• Accessories e riduzioni per cavi incluse nella confezione.</i>

MATERIAL CHARACTERISTICS

Body	PA66 GF UL94 V0 GWT 960°C
Connector housing	PA66 GF UL94 V0 GWT 960°C
Cable gland	PA66 UL94 V2 GWT 850°C
Sealing	Silicone
Grommets	TPE
Contacts	CuZn (nickel plated)



Screws	Steel (rivestimento Ottone)
Material properties	Halogen Free
T marking	T 85°C
Operating temperature range	-40°C / +125°C
Proof Tracking Index (PTI)	PTI 175

i Contact our Customer Service for more information on additional tests and approvals.

INDUSTRY STANDARDS

Standard number	EN 60998-1:2004; EN 60529:1991
------------------------	--------------------------------

PACKAGING INFORMATION

Packaging method	single packed unit
Quantity (product/bag)	1 product/bag
Quantity (product/box)	50 bags/box
Unit weight	76,6 gram/bag
Box dimension	400 x 210 x 170

i Accessorises and installation instructions included in the kit.