



The image has the only illustrative purpose and it is purely indicative, it may not fully reflect the product configuration.

# Mini IoTH Junction Box 6 ways M16/M20 - Zhaga Book 18

Code: IOTH.212.Z000















Potential improvements of the product and modifications of the technical data contained in this document can be made without notice.

#### **GENERAL INFORMATION**

| Type of installation    | Joint connector (re-usable/re-accessible)                        |  |
|-------------------------|--|--|
| Product configuration   | Junction box (empty)   |  |
|                         | *Zhaga book 18 adapter included in the package.                  |  |
| Colour                  | Black (Plastic - Rubber components) - White (Silicon components) |  |
| Overall dimensions (mm) | 72.0 x 75.0 x 57.0   |  |
| Connector shape         | Straight   |  |
|                         |  |  |

#### **ELECTRIC DATA**

| No. connected cables   | 6  |
|------------------------|--|
| Circuit wiring diagram | Power/Signal                                 |
| Voltage rating (AC/DC) | 30V DC                                       |
|                        | *Rated Current: 1.5A                         |
| No. poles              | 4  |
| Marking                | 1-2-3-4                                      |
|                        | *For connection scheme see instruction sheet |

#### **CONNECTION DATA**

| *Cable type: Ø 0.5mm H05V2           |        |
|--------------------------------------|--------|
| Cable diameter MIN (mm)              | 0.50   |
| Cable diameter MAX (mm)              | 1.00   |
| Tightening torque of nut-cable gland | 2.5 Nm |

#### **ENVIRONMENT CONDITIONS**

| IP rating   | IP20, IP66  |
|---|---|
|   | *IP66 guaranteed with the use of the cap 603002200 (not included in the kit) placed over the Zhaga Book 18 connector (Max. Tightening 2.5 Nm) |
| IK rating   | IK08  |
| Ambient temperature MIN/MAX (Accord to EN61984/EN60998) | ling -20°C/+60°C  |
| Operating temperature MAX                               | +60°C   |

#### **MATERIALS**

| Exterior body     | PC/ABS UL94V0        |
|-------------------|----------------------|
| Connector         | PBT                  |
| O Rings           | Silicone / TPE       |
| Material property | Halogen Free (TH212) |

#### **COMMERCIAL DATA**

| EAN                  | 8057457098991       |
|----------------------|---------------------|
| Packing method       | Bulk packed ( OEM ) |
| Type of packaging    | Blister             |
| Kit contents         | △ IOTH.212.Z000.pdf |
| Pieces/kit (pcs)     | 1                   |
| Custom tariff number | 85369010            |

#### **APPROVALS**

Please login to access this data.

## **TECHNICAL DOCUMENTATIONS**

#### **Technical documentations:**

| File                              | Туре | Size      |
|-----------------------------------|------|-----------|
| △ 606002052_IST_IOTH212_ZHAGA.pdf | PDF  | 946.84 KB |
| ☐ ITA_ANNEX_TH212.pdf             | PDF  | 8.57 MB   |

### **DRAWINGS**

## Drawings:

| File                | Туре | Size      |
|---------------------|------|-----------|
| ☑ IOTH.212.Z000.pdf | PDF  | 226.41 KB |

#### **CAD FILES**

Please login to access this data.