



The image has the only illustrative purpose and it is purely indicative, it may not fully reflect the product configuration.

Junction box 4 ways M16 IP66/IP67/IP68

Code: **THA.210.B0A**



Potential improvements of the product and modifications of the technical data contained in this document can be made without notice.

GENERAL INFORMATION

Type of installation	Joint connector (re-usable/re-accessible)
Product configuration	Junction box (empty) <i>*Cable accessories and terminal block to be ordered separately</i>
Colour	Black (Plastic components) - Techno green (Rubber components)
Overall dimensions (mm)	150.0 x 130.0 x 42.0
Inner dimensions (mm)	100 x 83 x 34

ELECTRIC DATA

No. connected cables	4
----------------------	---

CONNECTION DATA

Tightening torque of Lid/Fixing screws	0.8 Nm
--	--------

ENVIRONMENT CONDITIONS

IP rating	IP66, IP67, IP68
	<i>*IP68 (5m/1h)</i>
Salt Mist	Salt mist test : EN60068-2-11:2000
Ambient temperature MIN/MAX (According to EN61984/EN60998)	-40°C/+100°C
Operating temperature MAX	+60°C

MATERIALS

Exterior body	PA66 UL94 V2
O Rings	TPE
Material property	Halogen Free - Silicone Free
Lid/Fixing screws	Steel

PRODUCT COMPLIANCES

IEC Approvals	EN 60529:1991 - EN 60998-1:2004
---------------	---------------------------------

COMMERCIAL DATA


EAN	8057457098465
Packing method	Bulk packed (OEM)
Type of packaging	Box
Pieces/box (pcs)	10
Weight per Piece (gr)	145.00
Overall dimensions of box (mm)	400 x 210 x 170
Custom tariff number	85369010
Country of origin	ITALY

APPROVALS

Please login to access this data.


TECHNICAL DOCUMENTATIONS

Technical documentations:

File	Type	Size
 606002041_TH210_web.pdf	PDF	1.38 MB

DRAWINGS

Drawings:

File	Type	Size
 THA_210_B0A.pdf	PDF	302.97 KB

CAD FILES

Please login to access this data.

MARKETING DOCUMENTS

Please login to access this data.