


Synthetic protective conduit liquid-tight



Synthetic protective conduit liquid-tight

- Synthetic protective conduit liquid-tight
- AIRflex®-KUW-PU-AS
- Metallic blue

| | |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Order number: | 2040.701.038 |
| E-No: | 125280702 |
| EAN: | 7611614059600 |
| Material | Polyurethane jacket, inside helix of plastic sheathed spring steel wire |
| Properties | Extremely flexible, highly expansible and upsettable, airtight and liquid-proof, high tenacity and abrasion resistance, oil-, petrol- and grease-resistant, widely resistant to solvents and acids, free of halogen, silicone and cadmium, microbe resistant, o |
| Application | Machine and plant constructions, vehicle construction, shipbuilding, automation, electrical installations |
| Tested acc. to | EN / IEC 61386-23 |
| Protection class | IP 68 |
| Operation temperature | -40°C / +100°C / ^ +120°C |
| Outer diameter | 45 mm |
| Inner diameter | 38 mm |
| Bending radius static | 36 mm |
| Bending radius dynamic | 90 mm |
| Bushing | 5020.030.036 |
| Dispatch | 25 |