

Part number

CDF 08



Female insert, CD series, crimp connection, 8 poles, 10 A 50 V 0,8 kV 3, size "21.21"

Product description		Material properties	
Product type	Insert	Main material	Polycarbonate (PC)
Series	CD	Colour	RAL 7032 grey
Connection type	Crimp connection		Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
Gender	Female	RoHs conformity	
N. of poles	8 poles	China RoHs - EFUP	E
Size	Size "21.21"	REACH SVHC substances	Yes Lead
Technical data		Approvals / Standards	
Current	10 A	Reference standard	EN 61984:2009-06
Voltage	50 V	Certifications	CSAc, CQC, DNV-GL, BV, EAC
Rated impulse withstand voltage	0,8 kV	UL	ECBT2
Pollution degree	3	cUL	ECBT8
Rated voltage according to UL/CSA	50 V AC/120 V DC	General ordering information	
IP degree of protection	IP20 without enclosure, IP44/IP66/IP67/IP68/IP69 with enclosure	EAN13 code	8015747014335
Further technical details		eCl@ss 8.1	27440205
Characteristics according to EN 61984	10A 50V ac / 120 dc 0,8kV 3	ETIM 7.0	EC000438
Mating cycles	≥ 500	Packaging Information	
Insulation resistance	≥ 10 GΩ	Packaging length	210,00 mm
Contact resistance	≤ 3 mΩ	Packaging height	200,00 mm
Weight	9,50 g	Packaging width	130,00 mm
Operating temperature range (min, max)	-40 °C ... +125 °C	Packaging weight	2,17 kg
Conductors stripping length	8 mm (6 mm for 2,5 mm ²)	Packaging volume	5,46 dm ³
UL 94 flammability rating	V-0	Packaging description	Carton box
Tightening torque for PE connection	M4: 1,2 Nm, 10,6 lb.in (Ph2 or 1,0x5,5mm)	Packaging quantity	200 Pcs
Tightening torque for fixing screws	M3: 0,5 Nm; 4,4 lb.in (Ph1 or 0,8 x 5,5 mm)	Packaging EAN code	8015747103220
		Sub-packaging weight	0,43 kg
		Sub-packaging description	Carton tray
		Sub-packaging quantity	40 Pcs
		Sub-packaging EAN barcode	8015747103237


Part number

CDF 08



Catalogue drawings


CDM 08



CDF 08



Catalogue drawings



Notes

Dimensions shown in mm are not binding and may be changed without notice.

CDA ... : for non-prepared conductors



CDA ... X : for conductors with bush terminal