



TH026 - Linear compact mini-connector





















GENERAL DESCRIPTION

Type of installation	Joint connector (re-usable/re-accessible)
Type of product (Family)	TEEBLOCK® - Linear compact connectors
Product name (Series)	TH026 - Linear compact mini-connector
Product configuration	In-line joint connector
Colour	marrone RAL7021
Outer dimension	32 mm x 21 mm x 16.4 mm

ELECTRICAL CHARACTERISTICS

Number of poles	5
Contact marking	E - L - N - 1 - 2
Type of connection	screw with push-wire clamp (M3 - max. 0.5 Nm) • Recommnded for cable of cross-section < 1.0 mm².
Operating current	max. 24A
Operating voltage	max. 450V AC

Contact our Customer Service for availability of other markings.

MECHANICAL CHARACTERISTICS

Protection against solid/water (IP)	IP00
Corrosion resistance	Salt mist, 1.000 ore, 5% salt solutions, 35°C EN60068-2-11:2000, Test Ka (168h)
Contact our Customer Service for av	ailability of products with different IP and IK protection degrees.

CABLE CHARACTERISTICS

Wire cross-section min max. (Stranded cable)	0.5 mm ² - 2.5 mm ² • Tested positively with cables of cross-section 0.25 mm ²
Wire cross-section min max. (Solid cable)	0.5 mm ² - 2.5 mm ² • Tested positively with cables of cross-section 0.25 mm ²

MATERIAL CHARACTERISTICS

Body	PA66 GF UL94 V0 GWT 960°C
Contacts	CuZn (nickel plated)
Screws	Steel (rivestimento Zinco)
Material properties	Halogen Free - Silicone Free
T marking	T 125°C
Operating temperature range	-40°C/+125°C

① Contact our Customer Service for more information on additional tests and approvals.

INDUSTRY STANDARDS Standard number

PACKAGING INFORMATION	
Packaging method	not assembled components

EN 60998-1:2004

page 1 of 2

© Techno s.r.l.

www.techno.it

CERTIFICATIONS AND TEST REPORTS

- IMQ TH026 A3X2G5 CA0203230 PDF • 215 KB
- **CE-TH026** DOC 143 KB

DOCUMENT ATION

• 07 techno catalogo teedrum teeblock 150dpi • 5 MB

DRAWINGS

- THB026A1ASTEP
 - 559 KB A CONFIDENTIAL DOCUMENT





Quantity (product/box)	400 products/box
Unit weight	13,6 gram/product
Box dimension	400 x 210 x 170