




## THB.026.B1A

TH026 - Linear compact mini-connector

MADE IN ITALY



### GENERAL DESCRIPTION

Type of installation	Joint connector (re-usable/re-accessible)
Type of product (Family)	TEEBLOCK® - Linear compact connectors
Product name (Series)	TH026 - Linear compact mini-connector
Product configuration	In-line joint connector
Colour	marrone RAL7021
Outer dimension	20.6 mm x 21 mm x 16.4 mm

### ELECTRICAL CHARACTERISTICS

Number of poles	3
Contact marking	L - E - N
Type of connection	screw (M3 - max. 0.5 Nm)
Operating current	max. 32A
Operating voltage	max. 450V AC

**i** Contact our Customer Service for availability of other markings.

### MECHANICAL CHARACTERISTICS

Protection against solid/water (IP)	IP00
Corrosion resistance	Salt mist, 1.000 ore, 5% salt solutions, 35°C EN60068-2-11:2000, Test Ka (168h)

**i** Contact our Customer Service for availability of products with different IP and IK protection degrees.

### CABLE CHARACTERISTICS

Wire cross-section min. - max. (Stranded cable)	0.5 mm <sup>2</sup> - 4.0 mm <sup>2</sup>
Wire cross-section min. - max. (Solid cable)	0.5 mm <sup>2</sup> - 4.0 mm <sup>2</sup>

### MATERIAL CHARACTERISTICS

Body	PA66 GF UL94 V0 GWT 960°C
Contacts	CuZn (nickel plated)
Screws	Steel (rivestimento Zinco)
Material properties	Halogen Free - Silicone Free
T marking	T 125°C
Operating temperature range	-40°C/+125°C

**i** Contact our Customer Service for more information on additional tests and approvals.

### INDUSTRY STANDARDS

Standard number	EN 60998-1:2004
-----------------	-----------------

### PACKAGING INFORMATION

Packaging method	not assembled components
Quantity (product/box)	400 products/box

### CERTIFICATIONS AND TEST REPORTS

- IMQ TH026 A3X2G5 CA0203230  
PDF • 215 KB
- CE-TH026 DOC • 143 KB

### DOCUMENTATION

- 07 techno catalogo teedrum teeblock 150dpi  
• 5 MB

### DRAWINGS

- THB026B1ASTEP  
• 309 KB • CONFIDENTIAL DOCUMENT



<b>Unit weight</b>	8,5 gram/product
<b>Box dimension</b>	300 x 200 x 160