

# **THB.026.B2A**

TH026 - Linear compact mini-connector

IPOO 🐼 C E 💁 🔬 🕥



MADE IN ITALY

## CERTIFICATIONS AND TEST REPORTS

- IMQ TH026 A3X2G5 CA0203230 PDF • 215 KB
- CE-TH026 DOC 143 KB

#### **DOCUMENTATION**

• 07 techno catalogo teedrum teeblock 150dpi • 5 MB

#### DRAWINGS

- THB026B1ASTEP
  - 309 KB 🔒 CONFIDENTIAL DOCUMENT

## **GENERAL DESCRIPTION**

Type of installation	Joint connector (re-usable/re-accessible)
Type of product (Family)	TEEBLOCK <sup>®</sup> - Linear compact connectors
Product name (Series)	TH026 - Linear compact mini-connector
Product configuration	In-line joint connector
Colour	marrone RAL7021
Outer dimension	20.6 mm x 21 mm x 16.4 mm

## **ELECTRICAL CHARACTERISTICS**

Number of poles	3
Contact marking	L - E - N
Type of connection	screw with push-wire clamp (M3 - max. 0.5 Nm) • Recomminded for cable of cross-section < 1.0 mm <sup>2</sup> .
Operating current	max. 24A
Operating voltage	max. 450V AC

Contact our Customer Service for availability of other markings.

#### MECHANICAL CHARACTERISTICS

Protection against solid/water (IP)	IP00
	Salt mist, 1.000 ore, 5% salt solutions, 35°C EN60068-2- 11:2000, Test Ka (168h)

Contact our Customer Service for availability of products with different IP and IK protection degrees.

### CABLE CHARACTERISTICS

Wire cross-section min max.	0.5 mm <sup>2</sup> - 2.5 mm <sup>2</sup>
(Stranded cable)	• Tested positively with cables of cross-section 0.25 mm <sup>2</sup>
Wire cross-section min max. (Solid cable)	0.5 mm <sup>2</sup> - 2.5 mm <sup>2</sup> • Tested positively with cables of cross-section 0.25 mm <sup>2</sup>

#### MATERIAL CHARACTERISTICS

Body	PA66 GF UL94 V0 GWT 960°C
Contacts	CuZn (nickel plated)
Screws	Steel (rivestimento Zinco)
Material properties	Halogen Free - Silicone Free
T marking	T 125°C
Operating temperature range	-40°C/+125°C

Contact our Customer Service for more information on additional tests and approvals.

## **INDUSTRY STANDARDS**

	page 1 of 2	last update 04/21/2017	© Techno s.r.l.	www.techno.it
Packaging method	not as	sembled components		
PACKAGING INFORMATION				
Standard number	EN 60	998-1:2004		
Oten dead assure have		000.4.000.4		

No responsibility is taken for the correctness of this information. All technical data or other eventual product modifications and improvements can be carried out without notice. The images are purely for information.





Quantity (product/box)	400 products/box
Unit weight	8,7 gram/product
Box dimension	300 x 200 x 160

No responsibility is taken for the correctness of this information. All technical data or other eventual product modifications and improvements can be carried out without notice. The images are purely for information.