

# Disconnects

- disconnects with lever
- possible to create parallel connections
- "Easy Bridge" system: multi-polar cross connection without the need for additional protections
- available in the colours: grey, beige, or in a version appropriate for use with "intrinsically safe" (Ex)i circuits (blue)
- maximum continual operating temperature 100°C



## grey version

## beige version

## (Ex)i version

## TECHNICAL CHARACTERISTICS

function/type	
rated cross-section	(mm <sup>2</sup> )
connecting capacity	
flexible	(mm <sup>2</sup> )
rigid	(mm <sup>2</sup> )
max. flexible with ferrule (mm) - ferrule type	
rated voltage / rated current / gauge	conf. to IEC 60947-7-1
rated voltage / rated current / AWG / tightening torque value	UL
(Ex e) rated voltage	(V)
rated impulse withstand voltage / pollution degree	
insulation stripping length	(mm)
tightening torque value (test / max)	(Nm)
height / width / thickness	TH/35 7.5 mm
height / width / thickness	TH/35 15 mm

## CBS.2/GR

## CBS.2

## CBS.2 (Ex)i

Cat. No.	CBS02GR
Cat. No.	CBS02
Cat. No.	CBS02I

disconnect lever	2
0.2 - 4	
0.2 - 4	
2 - WP25/14	
630V / 22A / A3	
600 V / 20 A / 20-12 AWG / 3.5 lb.in.	
-	
6 KV (*) / 3	
9	
0.4 / 0.6	
52 / 57 / 5	
60 / 57 / 5	



## CBS.4/GR

## CBS.4

## CBS.4 (Ex)i

Cat. No.	CBS04GR
Cat. No.	CBS04
Cat. No.	CBS04I

disconnect lever	4
0.2 - 6	
0.2 - 6	
4 - WP40/16	
630V / 24A / A4	
600 V / 24 A / 20-10 AWG / 4.4 lb.in.	
-	
6 KV / 3	
10	
0.5 / 0.8	
52 / 57 / 6	
60 / 57 / 6	



## APPROVALS

## ACCESSORIES

End sections	grey
	beige
	blue
"Easy Bridge" (PTC) cross connection (intrinsically IPXXB protected once mounted)	2 poles
	3 poles
Available also in coloured version (PTP)	5 poles
Ref. p. 131	10 poles
Coloured partition	red, green, white
Cross connection barrier	red
Marking tag	printed or blank
End bracket	

Type	Cat. No.
CB/PT/GR	CB401GR
CB/PT	CB401
CB/PT (Ex)i	CB402
PTC/2/02	PTC0202
PTC/2/03	PTC0203
PTC/2/05	PTC0205
PTC/2/10	PTC0210
PTC/2/00 (50 poles)	PTC0200
DFU/3	DU03
DFM/800	DF800 - DF 900
DFM/900	DF800 - DF 900
CNU/8/51	NU0851
BTU for PR/DIN and PR/3	BT005
BT/DIN/PO for PR/DIN only	BT001
BT/3-BTO for PR/3 only	BT003-BT007

Type	Cat. No.
CB/PT/GR	CB401GR
CB/PT	CB401
CB/PT (Ex)i	CB402
PTC/4/02	PTC0402
PTC/4/03	PTC0403
PTC/4/05	PTC0405
PTC/4/10	PTC0410
PTC/4/00 (42 poles)	PTC0400
DFU/3	DU03
DFM/800	DF800 - DF 900
DFM/900	DF800 - DF 900
CNU/8/61	NU0861
BTU for PR/DIN and PR/3	BT005
BT/DIN/PO for PR/DIN only	BT001
BT/3-BTO for PR/3 only	BT003-BT007