



# On two levels

## with UL94V-0 polyamide insulating body


- three level - for sensors
- with LOCK system
- suited for LED indication
- to be mounted onto PR/3 type rails - according to IEC 60715 Std., "TH/35" types
- available in grey RAL 7042 and beige RAL 1001 colours



TLS.2/T



TLS.2/U



LOCK system

TLS.2/T Cat. No. TL120 (with green LED between upper and intermediate levels)

TLS.2/U Cat. No. TL110 (with green LED between upper and lower levels)

The /GR tag indicates the grey colour version.

<b>grey version</b>	
<b>beige version</b>	
<b>(Ex)i version</b>	
<b>TECHNICAL CHARACTERISTICS</b>	
function / type	
rated cross-section	(mm <sup>2</sup> )
connecting capacity	
flexible	(mm <sup>2</sup> )
rigid	(mm <sup>2</sup> )
max. flexible with ferrule (mm <sup>2</sup> )-ferrule type	
rated voltage / rated current / gauge	conf. to IEC 60947-7-1
rated voltage / rated current / AWG / tightening torque value	UL (Ex e) rated voltage  /  (V)
rated impulse withstand voltage / pollution degree	
insulation stripping length	(mm)
tightening torque value (test / max)	(Nm)
height / width / thickness	TH/35 7,5 mm
height / width / thickness	TH/35 15 mm
height / width / thickness	G32

<b>TLS.2/GR</b>	Cat. No. <b>TL100GR</b>
<b>TLS.2</b>	Cat. No. <b>TL100</b>
three level - for sensors	
2,5	
0,2 ÷ 4	
0,2 ÷ 4	
2,5 - WP25/14	
250 V / 24 A / A3	
600 V / 15 A / 20-12 AWG / 3,5 lb.in	
-	
4 kV / 3	
8	
0,4 / 0,8	
52 / 62,5 / 6,2	
60 / 62,5 / 6,2	
-	

For the installation on limited longitudinal space where high density wiring is needed together with reliable insulation, special feed-through two/three level terminal blocks are available. The three level terminal blocks are suitable for circuits which are to be used and connected with specific equipment, as for example proximity sensors. In fact with the combined use of TLS.2 and TLD.2 terminal block, both the feeding and the signal carrying conductors of the proximity sensors can be economically and efficiently connected.

Particularly in the **TLS.2** terminal block, the intermediate and lower levels can be used to feed the sensors in d.c.; the feeding is distributed on the adjoining elements of the terminal board by means of a special **LOCK** connection system.

The above mentioned conducting bodies have a fork, pointed towards the exterior of the terminal block, which connects to the homologous element of the adjoining terminal block. The tightening of the resulting electrical contact is by means of a screw, already inserted in the threaded hole of the conducting bodies.

**The LOCK system, above described, allows the connection of positive and negative poles, without the use of any other parallel cross connection.** The conductors carrying the return signal from the sensor is connected to the upper feed-through level; the insertion, in the appropriate grooving of **PRP/5** coloured covers avoids any possible contact with the live parts, and allows an immediate identification of the polarity (Red for +, Blue for -).

**TLD.2** terminal block is perfectly compatible with the **TLS.2** for the connection of proximity sensors, as it has the same electrical and mechanical characteristics. Two of six tightening units can be connected to the sensor feeding cables and distribute the power supply to the other sensors.

**The cross-connection between the intermediate and lower levels of these terminal blocks to the contiguous ones of the TLS.2 can be performed by means of the two screws provided in the fork type conducting bodies of the TLS.2 – the first of the series – free from whatever connection; between the TLD.2 and TLS.2 terminal blocks a TLD/PI intermediate end section must be interposed, to ensure electric insulation of the TLD.2 terminal block conducting parts, which otherwise would be uncovered.**

TLD.2 terminal block can also be used for other connecting applications, in other types of circuits.

### APPROVALS



### ACCESSORIES

End sections	grey beige blue
Permanent cross connection	
Rated current carrying capacity of jumper	(A)
Switchable cross connection	
Multiple common bar	250 mm
Shunting screw and sleeve	
Coloured partition	red, green, white
Cross connection barrier	red
Test plug socket	
Test plug	
Modular test plug	
End section for modular test plug	
Numbering strip	
Warning plate	on adjacent terminal blocks
Cover for cross-connection	
Marking tag	printed or blank
End bracket	
Mounting rail	
according to IEC 60715 Std.	

Type	Cat. No.
TLS/PT/GR	TL101GR
TLS/PT	TL101
PM/20/2 poles	PM202
PM/30/3 poles	PM303
PM/30/5 poles	PM305
PM/30/10 poles	PM310
24	
POS/41	POS41
PMP/02	PMP02
CPM/21	CPM21
DFU/3	DU03..
DFM/400	DF400
PSD/D	PD004
SDD/1	DD001
-	
-	
-	
-	
PRP/5	PRP05
CNU/8/51	NU0851
BTU for PR/DIN and PR/3	BT005
BTO for PR/3 only	BT007
BT/3 for PR/3 only	BT003
PR/3/AC for PR/DIN and PR/3	PRO03
PR/3/AS same with slots	PRO05