




Model	Rated current (A)	Rated voltage (V)	Rated power (W)
BPL.4	32	500	16000
BPL.4	32	300	9600
BPL.4	32	250	8000
BPL.4	32	200	6400
BPL.4	32	150	4800
BPL.4	32	100	3200
BPL.4	32	75	2400
BPL.4	32	50	1600
BPL.4	32	25	800
BPL.4	32	15	480
BPL.4	32	10	320
BPL.4	32	5	160

Il prodotto è conforme alla direttiva CE 2006/95/CE e alla direttiva CE 2004/109/CE. Il prodotto è conforme alla direttiva CE 2006/66/CE e alla direttiva CE 2002/95/CE. Il prodotto è conforme alla direttiva CE 2002/95/CE e alla direttiva CE 2002/95/CE. Il prodotto è conforme alla direttiva CE 2002/95/CE e alla direttiva CE 2002/95/CE.

modular multi-pole terminal, 4 mm<sup>2</sup>, beige

<b>Series</b>	BPL-TPL
<b>Code</b>	BP200
<b>Type</b>	BPL/R
<b>HS code</b>	85369010
<b>Colour</b>	Beige
<b>TECHNICAL FEATURES</b>	
<b>Function/Type</b>	Feed-through 2 poles
<b>Rated cross-section</b>	4 mm <sup>2</sup>
<b>Rated cross-section</b>	
<b>Connecting capacity</b>	
<b>Flexible wire</b>	0.5-4 mm <sup>2</sup>
<b>Rigid wire</b>	0.5-6 mm <sup>2</sup>
<b>Wire with ferrule - ferrule type</b>	4 mm <sup>2</sup> - WP40/16
<b>Electrical characteristics according to IEC EN standard</b>	
<b>Maximum voltage AC/DC</b>	500 V
<b>Maximum current (rated cross-section)</b>	32 A
<b>Caliber</b>	A4
<b>Electrical characteristics according to UL Standard</b>	
<b>Maximum voltage AC/DC</b>	300 V
<b>Maximum current (rated cross-section)</b>	20 A
<b>Section (min-max)</b>	18-12 (AWG)
<b>Tightening torque value (UL)</b>	4.4 lb.in
<b>Electrical characteristics according to ATEX directive and IEC Ex standard</b>	
<b>Maximum voltage AC/DC</b>	320 V
<b>Maximum current (rated cross-section)</b>	32 A
<b>Operating temperature Min/Max</b>	-40 °C / +110 °C
<b>Rated impulse withstand voltage / pollution degree</b>	6 kV / 3
<b>Insulation stripping length</b>	9 mm
<b>Tightening torque value (nom. / max.)</b>	0.5 / 0.7 Nm
<b>Dimension</b>	13x24x26 mm (AxBxH)
<b>Insulation material temperature index (EN 60216-1)</b>	130 °C
<b>Plastic material</b>	Polyamide UL94V-0
<b>ACCESSORIES</b>	
<b>End section</b>	-
<b>Insulated bushing</b>	-
<b>APPROVALS AND MARKINGS</b>	Ex, RoHS, REACH



\* Panel mountable with M3 screw (max. 5.6 mm head diameter)\* With dovetail joint for multiple connection  
1 (1) When using BPL.4 and TPL.4 terminal blocks in Ex e classified installations, is required the insulated fixing screw

## DESCRIZIONE DEL PRODOTTO

modular multi-pole terminal, 4 mm<sup>2</sup>, beige