




## screw terminal block 2 levels fuse-holder, 4 mm<sup>2</sup>, grey

<b>Series</b>	MPFA-DSFA
<b>Code</b>	DA100GR
<b>Type</b>	DSFA.4/GR
<b>HS code</b>	85369010
<b>Colour</b>	grey
<b>TECHNICAL FEATURES</b>	
<b>Function/Type</b>	2 levels (fuse-holder + feed-through)
<b>Rated cross-section</b>	4 mm <sup>2</sup>
<b>Connecting capacity</b>	
<b>Flexible wire</b>	0.2-6 mm <sup>2</sup>
<b>Rigid wire</b>	0.2-6 mm <sup>2</sup>
<b>Wire with ferrule - ferrule type</b>	4 mm <sup>2</sup> - WP40/16
<b>Electrical characteristics according to IEC EN standard</b>	
<b>Maximum voltage AC/DC</b>	400 V
<b>Maximum current (rated cross-section)</b>	10 A (1) / 32 A
<b>Caliber</b>	A4
<b>Electrical characteristics according to UL Standard</b>	
<b>Maximum voltage AC/DC</b>	300 V
<b>Maximum current (rated cross-section)</b>	6.3-30 A
<b>Section (min-max)</b>	26-10 (AWG)
<b>Tightening torque value (UL)</b>	4.4 lb.in
<b>Electrical characteristics according to ATEX directive and IEC Ex standard</b>	
<b>Rated impulse withstand voltage / pollution degree</b>	6 kV / 3
<b>Insulation stripping length</b>	9 mm
<b>Tightening torque value (nom. / max.)</b>	0.5 / 1.2 Nm
<b>Width (pitch)</b>	6 mm
<b>Length</b>	78 mm
<b>Height mounted on TH35-7.5/TH35-15/G32</b>	68 / 75 / 72 mm
<b>Insulation material temperature index (EN 60216-1)</b>	130 °C
<b>Plastic material</b>	Polyamide UL94V-0
<b>ACCESSORIES</b>	
<b>End section</b>	
<b>Grey</b>	DSS/PT/GR (cod. DS301GR)
<b>Blue</b>	-
<b>Beige</b>	DSS/PT (cod. DS301)
<b>Thickness</b>	1.5 mm
<b>Cross-connection</b>	
<b>Model A)</b>	PTC/4/... (cod. PTC04...)
<b>Model B)</b>	-
<b>Rated current carrying capacity IEC/ATEX</b>	33 A
<b>Cross-connection identification strip</b>	-
<b>Coloured partition plate</b>	DFU/7/R (cod. DU07R)
<b>Cross-connection barrier</b>	DFM/500 (cod. DF500)
<b>Test plug socket</b>	-
<b>Test plug</b>	-
<b>Marking</b>	
<b>Snap-on numbering strip</b>	CNU/8/51 (cod. NU0851S) - CNU/10/61 (cod. NU1061S)
<b>Single marking tag</b>	-
<b>Fuse type</b>	6.3x32 mm (1)
<b>Conductive element</b>	CO/6 (cod. CO06)
<b>Light alarm circuit (12...48 V)</b>	-
<b>Light alarm circuit (110...230 V)</b>	-
<b>Cartridge</b>	CPF/5 (CPF05)
<b>End bracket</b>	
<b>TH35 screw type</b>	BT/3 (cod. BT003)
<b>TH35 snap-fit type</b>	BTO (cod. BT007)
<b>TH35 and G32 snap-fit type</b>	BTU (cod. BT005)
<b>Mounting rail</b>	
<b>IEC 60715/TH35</b>	PR/3/...
<b>IEC 60715/G32</b>	-
<b>APPROVALS AND MARKINGS</b>	



**DSFA.4** - detail of the terminal blocks with numbering CNU8B and CNU10B, leads side and view of the PTC4 cross connections on the upper level, lightgreen from the front and on the lower level.  
The terminal block can be supplied already including a non-polarised LED warning circuit, to warn if the base breaks.  
Two versions are available, depending on the different power supply voltages.  
**DSFA.4L12** code DA112 (complete with non-polarised 12 V LED circuit)  
**DSFA.4L24** code DA124 (complete with non-polarised 24 V LED circuit)





\* Suitable for "blade" fuses (DIN 72581/3F - ISO 8820) or 5x20 mm with CPF05 accessory\* The blade fuse can be replaced by 5x20 mm fuses or electronic components, thanks to the accessory CPF05 (for details see the accessories chapter)\* Fuse and cartridge accessory, are available separately  
1 For more details on accessories, refer to the relevant chapters2 (1) Max. 10 A with VL103 short circuit bar, and max. 6.3 A with fuse

## DESCRIZIONE DEL PRODOTTO

screw terminal block 2 levels fuse-holder, 4 mm<sup>2</sup>, grey