



screw terminal block 1 level fuse-holder, 4 mm², beige

| | |
|---|--|
| Series | DSF |
| Code | DA200 |
| Type | DSF.4 |
| HS code | 85369010 |
| Colour | Beige |
| TECHNICAL FEATURES | |
| Function/Type | 2 levels (fuse-holder + feed-through) |
| Rated cross-section | 4 mm ² |
| Connecting capacity | |
| Flexible wire | 0.2-6 mm ² |
| Rigid wire | 0.2-6 mm ² |
| Wire with ferrule - ferrule type | 4 mm ² - WP40/16 |
| Electrical characteristics according to IEC EN standard | |
| Maximum voltage AC/DC | 800 V |
| Maximum current (rated cross-section) | 6.3 (10 A con CO/5) / 32 A (1) |
| Caliber | A4 |
| Electrical characteristics according to UL Standard | |
| Electrical characteristics according to ATEX directive and IEC Ex standard | |
| Rated impulse withstand voltage / pollution degree | 8 kV / 3 |
| Insulation stripping length | 9 mm |
| Tightening torque value (nom. / max.) | 0.5 / 1.2 Nm |
| Width (pitch) | 8 mm |
| Length | 79.5 mm |
| Height mounted on TH35-7.5/TH35-15/G32 | 69 / 77 / - mm |
| Insulation material temperature index (EN 60216-1) | 130 °C |
| Plastic material | Polyamide UL94V-0 |
| ACCESSORIES | |
| End section | |
| Grey | DSF.4/PT/GR (cod. DS401GR) |
| Blue | - |
| Beige | DSF.4/PT (cod. DS401) |
| Thickness | 1.5 mm |
| Cross-connection | |
| Model A) | - |
| Model B) | - |
| Rated current carrying capacity IEC/ATEX | - |
| Cross-connection identification strip | - |
| Maximum voltage AC/DC | 600 V |
| Maximum current (rated cross-section) | 6.3-20 A |
| Coloured partition plate | DFU/7/R (cod. DU07R) |
| Section (min-max) | 26-12 (AWG) |
| Cross-connection barrier | - |
| Tightening torque value (UL) | 4.4 lb.in |
| Test plug socket | - |
| Test plug | - |
| Marking | |
| Snap-on numbering strip | CNU/8/51 (cod. NU0851S) - CNU/10/61 (cod. NU1061S) |
| Single marking tag | - |
| Fuse type | 5x20 mm (1) |
| Conductive element | CO/5 (cod. VL103) |
| Light alarm circuit (12...48 V) | - |
| Light alarm circuit (110...230 V) | CIL/115-230 (cod. SF510) |
| End bracket | |
| TH35 screw type | BT/3 (cod. BT003) |
| TH35 snap-fit type | BTO (cod. BT007) |
| TH35 and G32 snap-fit type | BTU (cod. BT005) |
| Mounting rail | |
| IEC 60715/TH35 | PR/3/... |
| IEC 60715/G32 | - |
| APPROVALS AND MARKINGS | |
| | |



* Suitable for 5x20 mm fuses* Accessory with alarm LED, available separately* Suitable for optional cartridge with 1 A or 3 A diode
1 For more details on accessories, refer to the relevant chapters2 (1) 6.3 A with fuse or 10 A with CO/5 on upper level / 32 A on lower level

DESCRIZIONE DEL PRODOTTO

screw terminal block 1 level fuse-holder, 4 mm², beige