








spring clamp terminal block 1 level earth connection 4 mm²

| | |
|---|-----------------------------|
| Series | HTE |
| Code | HT250 |
| Type | HTE.4 |
| HS code | 85369010 |
| Colour | Yellow-green |
| TECHNICAL FEATURES | |
| Function/Type | Earth terminal blocks |
| Rated cross-section | 4 mm ² |
| Connecting capacity | |
| Flexible wire | 0.2-6 mm ² |
| Rigid wire | 0.2-6 mm ² |
| Wire with ferrule - ferrule type | 4 mm ² - WP40/16 |
| Electrical characteristics according to IEC EN standard | |
| Maximum current (rated cross-section) | - |
| Caliber | A4 |
| Electrical characteristics according to UL Standard | |
| Maximum voltage AC/DC | 600 V |
| Maximum current (rated cross-section) | - |
| Section (min-max) | 24-10 (AWG) |
| Electrical characteristics according to ATEX directive and IEC Ex standard | |
| Maximum voltage AC/DC | 500 V |
| Operating temperature Min/Max | -40 °C / +80 °C |
| Insulation stripping length | 12 mm |
| Width (pitch) | 6.2 mm |
| Length | 58 mm |
| Height mounted on TH35-7.5/TH35-15/G32 | 45 / 52 / - mm |
| Insulation material temperature index (EN 60216-1) | 130 °C |
| Plastic material | Polyamide UL94V-0 |
| ACCESSORIES | |
| End section | |
| Grey | HMT.4/PT/GR (cod. HM251GR) |
| Blue | - |
| Thickness | 1.5 mm |
| Cross-connection | |
| Cross-connection identification strip | PTC/SP (cod. PTC0990) |
| Coloured partition plate | DFH/1/R (cod. DH01R) |
| Cross-connection barrier | - |
| Test plug | SDD/1 (cod. DD001) |
| Modular test plug | - |
| End section for modular test plug | - |
| Marking | |
| Single marking tag | CNU/8/61 (cod. NU0861S) |
| Single marking tag for pitch insertion | - |
| End bracket | |
| TH35 screw type | BT/3 (cod. BT003) |
| TH35 snap-fit type | BT0 (cod. BT007) |
| TH35 and G32 snap-fit type | BTU (cod. BT005) |
| DIN rail according to IEC 60715/TH35 | PR/3/.. |
| APPROVALS AND MARKINGS | |
|       | |



1 For more details on accessories, refer to the relevant chapters

DESCRIZIONE DEL PRODOTTO

spring clamp terminal block 1 level earth connection 4 mm²