


SERIE		DESCRIZIONE		MATERIALE		DIMENSIONI		PESI	
Modello	Descrizione	Materiali	Dimensioni (mm)	Peso (g)	Dimensioni (mm)	Peso (g)	Dimensioni (mm)	Peso (g)	Dimensioni (mm)
TE0.4	TE0.4	PA66	52x60x15	1.2	52x60x15	1.2	52x60x15	1.2	52x60x15
TE0.4/PT	TE0.4/PT	PA66	52x60x15	1.2	52x60x15	1.2	52x60x15	1.2	52x60x15

screw terminal block 1 level earth connection, 4 mm²

Series	TE
Code	T0430
Type	TE0.4
HS code	85369010
Colour	Yellow-green
TECHNICAL FEATURES	
Function/Type	Earth terminal blocks
Rated cross-section	4 mm ²
Connecting capacity	
Flexible wire	0.2-6 mm ²
Rigid wire	0.2-6 mm ²
Wire with ferrule - ferrule type	4 mm ² - WP40/16
Electrical characteristics according to IEC EN standard	
Maximum voltage AC/DC	-
Maximum current (rated cross-section)	-
Caliber	A4
Electrical characteristics according to UL Standard	
Maximum voltage AC/DC	600 V
Maximum current (rated cross-section)	-
Section (min-max)	20-12 (AWG)
Tightening torque value (UL)	5.5 lb.in
Electrical characteristics according to ATEX directive and IEC Ex standard	
Maximum voltage AC/DC	-
Maximum current (rated cross-section)	32 A
Operating temperature Min/Max	-40 °C / +110 °C
Rated impulse withstand voltage / pollution degree	8 kV / 3
Insulation stripping length	14 mm
Tightening torque value (nom. / max.)	0.5 / 1.2 Nm
Width (pitch)	6,5 mm
Length	50 mm
Height mounted on TH35-7.5/TH35-15/G32	52 / 60 / - mm
Insulation material temperature index (EN 60216-1)	130 °C
Plastic material	Polyamide UL94V-0
ACCESSORIES	
End section	
Grey	-
Green	TE0.4/PT (cod. T0431)
Thickness	-
Cross-connection	
Marking	
Single marking tag	CNU/8/51 (cod. NU0851S) - CNU/10/61 (cod. NU1061S)
Single marking tag for pitch insertion	-
End bracket	
TH35 screw type	BT/3 (cod. BT003)
TH35 snap-fit type	BTO (cod. BT007)
TH35 and G32 snap-fit type	BTU (cod. BT005)
Mounting rail	
IEC 60715/TH35	PR/3/...
IEC 60715/G32	PR/DIN/...
APPROVALS AND MARKINGS	



DESCRIZIONE DEL PRODOTTO

screw terminal block 1 level earth connection, 4 mm²

