


SERIE		DESCRIZIONE		MATERIE PLASTICHE		MATERIE METALLICHE	
Modello	Descrizione	Materiali	Spessore	Materiali	Spessore	Materiali	Spessore
T0510	Terminali a vite per terra	PA66	1,5	Al	0,2	Al	0,2
T0511	Terminali a vite per terra	PA66	1,5	Al	0,2	Al	0,2
T0512	Terminali a vite per terra	PA66	1,5	Al	0,2	Al	0,2
T0513	Terminali a vite per terra	PA66	1,5	Al	0,2	Al	0,2
T0514	Terminali a vite per terra	PA66	1,5	Al	0,2	Al	0,2
T0515	Terminali a vite per terra	PA66	1,5	Al	0,2	Al	0,2
T0516	Terminali a vite per terra	PA66	1,5	Al	0,2	Al	0,2
T0517	Terminali a vite per terra	PA66	1,5	Al	0,2	Al	0,2
T0518	Terminali a vite per terra	PA66	1,5	Al	0,2	Al	0,2
T0519	Terminali a vite per terra	PA66	1,5	Al	0,2	Al	0,2

screw terminal block 1 level earth connection, 10 mm²

Series	TEC
Code	T0510
Type	TEC.10/0
HS code	85369010
Colour	Yellow-green
TECHNICAL FEATURES	
Function/Type	Earth terminal blocks
Rated cross-section	10 mm ²
Connecting capacity	
Flexible wire	1.5-16 mm ²
Rigid wire	1.5-16 mm ²
Wire with ferrule - ferrule type	10 mm ² - WP100/21
Electrical characteristics according to IEC EN standard	
Maximum voltage AC/DC	-
Maximum current (rated cross-section)	-
Caliber	B6
Electrical characteristics according to UL Standard	
Maximum voltage AC/DC	-
Maximum current (rated cross-section)	-
Section (min-max)	-
Tightening torque value (UL)	-
Electrical characteristics according to ATEX directive and IEC Ex standard	
Maximum voltage AC/DC	-
Maximum current (rated cross-section)	-
Rated impulse withstand voltage / pollution degree	8 kV / 3
Insulation stripping length	12 mm
Tightening torque value (nom. / max.)	1.2 / 1.9 Nm
Width (pitch)	10 mm
Length	44 mm
Height mounted on TH35-7.5/TH35-15/G32	52 / 60 / - mm
Insulation material temperature index (EN 60216-1)	130 °C
Plastic material	Polyamide UL94V-0
ACCESSORIES	
End section	
Grey	-
Green	-
Thickness	-
Cross-connection	
Marking	
Single marking tag	CNU/8/51 (cod. NU0851S) - CNU/10/61 (cod. NU1061S)
End bracket	
TH35 screw type	BT/3 (cod. BT003)
TH35 snap-fit type	BT0 (cod. BT007)
TH35 and G32 snap-fit type	BTU (cod. BT005)
Mounting rail	
IEC 60715/TH35	PR/3/...
IEC 60715/G32	-
APPROVALS AND MARKINGS	



* Same profile and dimensions of the corresponding terminals of the CBC and GPA series* No end plates required, already closed in yellow/green shells

DESCRIZIONE DEL PRODOTTO

screw terminal block 1 level earth connection, 10 mm²

