



The image has the only illustrative purpose and it is purely indicative, it may not fully reflect the product configuration.

# Micro Plug Connector saferlock 2p Screw D5.8-6.9 IP66/IP68/IP69

Code: **THB.381.A2B** 

























Potential improvements of the product and modifications of the technical data contained in this document can be made without notice.

### **GENERAL INFORMATION**

Type of installation	Plug and Socket connector	
Product configuration	Plug connector	
Locking mechanism	Push Pull	
Colour	Black (Plastic components) - Techno green (Rubber	
	components)	
Overall dimensions (mm)	Ø 14.0 x 53.0	
Overall dimensions when mated together (mm)	Ø 14.0 x 90.0	

## **ELECTRIC DATA**

No. connected cables	1
Circuit wiring diagram	Power/Signal
Current rating (AC/DC)	10A AC/DC
Voltage rating (AC/DC)	500V AC (3V-60V DC)
Double insulated (Class II)	250V
Impulse withstand voltage	4kV
No. poles	2
Marking	1-2
Terminations	Screw
Terminations Thread/Tightening	M2 - 0.2 Nm
torque	

## **CONNECTION DATA**

Multi-stranded conductor cross- section without ferrule MIN (mm²)	0.25
Multi-stranded conductor cross-	1.00
section without ferrule MAX (mm²)	
Conductor stripping length (mm)	10.00
Cable sheath stripping length (mm)	20.00
Reccomended types of cable	H05xxx/H07xxx
Cable diameter MIN (mm)	5.80
Cable diameter MAX (mm)	6.90
Tightening torque of nut-cable gland	1.5 Nm

### **ENVIRONMENT CONDITIONS**

*IP68 (30m/1h)  Salt Mist Salt mist test : EN60068-2-11:2000  Mating cycles 100 cycles  Ambient temperature MIN/MAX -40°C/+125°C  (According to EN61984/EN60998)
Mating cycles  100 cycles  Ambient temperature MIN/MAX -40°C/+125°C
Ambient temperature MIN/MAX -40°C/+125°C
(According to ENG1994/ENG0999)
(According to Englacy-Lindoaso)
Operating temperature MAX +60°C
Proof Tracking Index (PTI) PTI 175

#### **MATERIALS**

Connector	PA66 GF UL94 VO
Cable gland	PA66 GF UL94 V2
O Rings	TPE
Gaskets	TPE
Impulse withstand category	II
Pollution degree	2
Material property	Halogen Free - Silicone Free
Contacts	Brass
Contact screws	Steel

#### PRODUCT COMPLIANCES

**IEC Approvals** EN 61984:2009 - EN 61535

#### **COMMERCIAL DATA**

EAN	8057457092579
Packing method	Bulk packed ( OEM )
Type of packaging	Box
Pieces/box (pcs)	200
Weight per Piece (gr)	7.70
Overall dimensions of box (mm)	200 x 200 x 120
Custom tariff number	85369010
Country of origin	ITALY

#### **APPROVALS**

Please login to access this data.

#### **TECHNICAL DOCUMENTATIONS**

### **Technical documentations:**

File	Туре	Size	
△ 606002032_TH381.pdf	PDF	571.88 KB	

#### **CAD FILES**

Please login to access this data.

#### **MARKETING DOCUMENTS**

Please login to access this data.