



The image has the only illustrative purpose and it is purely indicative, it may not fully reflect the product configuration.

Mini Joint Connector 2p Screw D7-13.5 IP68

Code: THB.390.A1B



Potential improvements of the product and modifications of the technical data contained in this document can be made without notice.

Type of installation	Joint connector (re-usable/re-accessible)	
Product configuration	In-line connector	
Colour	Black (Plastic components) - Techno green (Rubber	
	components)	
Overall dimensions (mm)	Ø 32.0 x 90.0	

GENERAL INFORMATION

ELECTRIC DATA

No. connected cables	2
Circuit wiring diagram	Power/Signal
Current rating (AC/DC)	32A
Voltage rating (AC/DC)	450V AC
No. poles	2
Marking	L-N
Terminations	Screw
Terminations Thread/Tightening	M3 - 0.8 Nm
torque	

CONNECTION DATA

Multi-stranded conductor cross- section without ferrule MIN (mm²)	0.50
Multi-stranded conductor cross- section without ferrule MAX (mm²)	4.00
Solid conductor cross-section MIN (mm²)	0.50
Solid conductor cross-section MAX (mm²)	4.00
Conductor stripping length (mm)	8.00
Cable sheath stripping length (mm)	30.00
Reccomended types of cable	H05xxx/H07xxx
Cable diameter MIN (mm)	7.00
Cable diameter MAX (mm)	13.50
Tightening torque of cable gland- connector	2.5 Nm
Tightening torque of nut-cable gland	l 2.5 Nm

ENVIRONMENT CONDITIONS

IP rating	IP68	
	*IP68 (50m/1h)	
IK rating	IK07	
Salt Mist	Salt mist test : EN60068-2-11:2000	
T marking	T 125°C	
Proof Tracking Index (PTI)	PTI 250	

MATERIALS

Exterior body	PA66 GF UL94 VO
Connector	PA66 GF UL94 VO
Cable gland	PA66 UL94 V2
O Rings	Silicone
Gaskets	TPE
Material property	Halogen Free
Contacts	Brass
Contact screws	Steel

PRODUCT COMPLIANCES

IEC Approvals

EN 60998-1:2004

COMMERCIAL DATA

8057457093651
Bulk packed (OEM)
Box
200
40.30
400 x 400 x 230
85369010
ITALY

APPROVALS

Please login to access this data.

TECHNICAL DOCUMENTATIONS

Technical documentations:

File	Туре	Size
☐ 606001200_IST_I_TH390_400.pdf	PDF	1.48 MB

DRAWINGS

Drawings:

File	Туре	Size
THB_390_AXA.pdf	PDF	291.94 KB

CAD FILES

Please login to access this data.

MARKETING DOCUMENTS

Please login to access this data.