



The image has the only illustrative purpose and it is purely indicative, it may not fully reflect the product configuration.

Mini Joint Connector 2p WP D7-12 IP68

Code: THB.391.A2C



Potential improvements of the product and modifications of the technical data contained in this document can be made without notice.

Type of installation	Joint connector (re-usable/re-accessible)	
Product configuration	In-line connector	
Colour	Black (Plastic components) - Techno green (Rubber components)	
Overall dimensions (mm)	Ø 23.0 x 66.0	

GENERAL INFORMATION

ELECTRIC DATA

2
Power/Signal
24A
450V AC
2
1-2
Screw with wire protector
M3 - 0.8 Nm

CONNECTION DATA

Multi-stranded conductor cross- section without ferrule MIN (mm²)	0.25
Multi-stranded conductor cross- section without ferrule MAX (mm²)	2.50
Conductor stripping length (mm)	6.00
Cable sheath stripping length (mm)	20.00
Reccomended types of cable	H05xxx/H07xxx
Cable diameter MIN (mm)	7.00
Cable diameter MAX (mm)	12.00
Cable diameter MAX (mm) Tightening torque of cable gland- connector	12.00 2.0 Nm

ENVIRONMENT CONDITIONS

IP rating	IP68
	*IP68 (30m/2h)
IK rating	IK07
Salt Mist	Salt mist test : EN60068-2-11:2000
T marking	T 85°C
Proof Tracking Index (PTI)	PTI 250

MATERIALS

Connector	PA66 GF UL94 VO	
Cable gland	PA66 UL94 V2	
O Rings	TPE	
Gaskets	TPE	
Material property	Halogen Free - Silicone Free	
Contacts	Brass	
Contact screws	Steel	

PRODUCT COMPLIANCES

IEC Approvals

EN 60998-1:2004

COMMERCIAL DATA

EAN	8057457093781
Packing method	Bulk packed (OEM)
Type of packaging	Вох
Pieces/box (pcs)	200
Weight per Piece (gr)	20.30
Overall dimensions of box (mm)	400 x 210 x 170
Custom tariff number	85369010
Country of origin	ITALY

APPROVALS

Please login to access this data.

TECHNICAL DOCUMENTATIONS

Technical documentations:

File	Туре	Size
☐ 606003900_IST_TH391.pdf	PDF	1.59 MB
DRAWINGS		
Drawings:		
File	Туре	Size
占 THB_391_AXA.pdf	PDF	288.89 KB

CAD FILES

Please login to access this data.

MARKETING DOCUMENTS

Please login to access this data.